

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Dansani

Supplier's address: Dansani, Finlandsvej 8, 6100 Haderslev, DK

Model identifier: 93461 Panorama 60

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	No cap-type		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters


Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	6	Energy efficiency class	E
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	759 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2100...6500
On-mode power (P_{on}), expressed in W	5,9	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	91
Outer dimensions without separate control gear, light-	Height	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width		
	Depth		

ing control parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,316 0,336	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	70	Survival factor	0,90	
the lumen maintenance factor	0,96			

(a) '-': not applicable;

(b) '-': not applicable;

Spectrum Test Report



Color Parameters:

Chromaticity Coordinate: $x=0.3163$ $y=0.3356$ $u'=0.1978$ $v'=0.4723$
CCT=6277K(Duv=0.0048) Dominant WL:Ld =493.4nm Purity=5.6%
Ratio:R=15.0% G=78.1% B=6.9% Peak WL:Lp=455.8nm FWHM=24.9nm
Render Index:Ra=91.8
R1 =93 R2 =99 R3 =97 R4 =86 R5 =90 R6 =94 R7 =90
R8 =86 R9 =70 R10=94 R11=88 R12=63 R13=96 R14=99 R15=90

Photo Parameters:

Flux = 759.2 lm Eff. : 128.97 lm/W η_e = 2.576 W

Electrical parameters:

V = 12.000 V I = 0.4906 A P = 5.887 W PF = 1.000

LEVEL:OUT WHITE:ANSI_6500K

Status: Integral T = 720 ms I_p = 42760 (65%)

Model:MLE06T-A-6500K-LED(144PCS) Number:4
Tester:ZW Date:2022-01-18
Temperature:25.3Deg Humidity:65.0%
Manufacturer:GB Remarks:SE001497

Model placed on the Union market from 02/01/2022



EPREL registration number: 1305588

<https://eprel.ec.europa.eu/qr/1305588>

Supplier: Dansani A/S (Manufacturer)

Website:

Customer care service:

Name: Dansani

Website: www.dansani.dk

Email: sba@dansani.dk

Phone: +4523829794

Address:

Finlandsvej 8
6100 Haderslev
Denmark