



STANDARD OR SELF-TEST EMERGECY CONVERSION PACK WITH LITHIUM (LiFePO4) BATTERY - SEE PAGE 29



OPTIONAL MOUNTING DISC. FOR RETROFIT INSTALLATION INTO EXISTING HOLES UP TO 200MM DIA.

APPLICATIONS

- Meeting rooms

- Reception areas

CONSTRUCTION

- PC front bezel

- Opal PC diffuser

- Remote driver

- Offices

- Toilets

- Corridors & circulation areas

- PC semi-specular reflector

- Die-cast aluminium heat sink

WESTPORT

Low glare commercial fixed downlighter















- 145 lm/W
- 2 wattages available:

TECHNICAL DETAILS

- 12W, 1,755 lumens, 122 l.lm/c.W
- · 24W, 2,786 lumens, 116 l.lm/c.W
- CRI >80
- CCT 4000K
- LEDs on metal core PCB
- Branded ENEC approved, flicker free, LED driver

OPTIONS

EMERGENCY Plug-in lithium emergency conversion pack. To be ordered separately, as listed below.

SPECIALIST EMERGENCY DALI Addressable Emergency (Suffix DAM3) options available.

DIMMING DD (DALI or Switch Dim) or CF (Corridor Function) available. Add suffix DD or CF as required.

MOUNTING DISC Allows retrofit installation into existing holes up to 200mm diameter

ORDER CODE	DESCRIPTION
NWP12/840	Westport 12W LED Recessed Downlight 840
NWP24/840	Westport 24W LED Recessed Downlight 840
ACCESSORIES	
NWP/MOUNTING/DISC	Westport Mounting Disc for cutouts upto 200mm dia. White
N/REC/M3/PACK/V2	M3 Pack V2 LiFePO4 for Recessed Product Ranges
N/RFC/STM3/PACK/V2	M3 Pack V2 Self-test LiFePO4 for Recessed Product Ranges

