

## ROREC PRO Digital

### Refrigerant recovery device

Lightweight recovery unit for the recovery of refrigerants of the classes A1, A2L and A2 (incl. R32), suitable for all unit sizes thanks to its high recovery rate.



### Product profile

#### KEY FEATURES

- Suitable for refrigerants of the classes A1, A2L and A2 (incl. R32)
- Compact design with a weight of less than 12 kg
- Digital display and one-knob control
- Maintenance free operation with the oil-free 2-piston compressor
- 4-pole motor guarantees the durability of the machine
- Automatic shut-off and automatic restart once the pressure increases again
- Emptying of refrigerant residues with the PURGE function

#### TECHNICAL DATA

<b>Recovery rate:</b>	gaseous:	0.5 kg / min; 30 kg / h
	fluid:	3.5 kg / min; 210 kg / h
	push/pull:	9.5 kg / min; 570 kg / h
<b>Power supply:</b>	230 V / 50 - 60 Hz	
<b>Power:</b>	730 W	
<b>High pressure switch:</b>	38.5 bar	
<b>Product dimensions:</b>	380 x 250 x 350 mm	
<b>Weight:</b>	12 kg	

#### Digital display

Clearly structured display of the measured pressure values

#### Low pressure switch

Automatic shut-off and automatic restart once the pressure increases again

#### Oil-free 2-piston compressor

Very high recovery rate with maintenance free operation



Shoulder strap for transport over longer distances



Clearly structured digital display



Model	kg		No.
ROREC PRO Digital	12.0	1	1500002637
Filter	0.12	1	168713