



DATASHEET

WESTPORT

Westport Fixed Output Driver For 12W c/w 3-Pole Connector Block

12W Fixed output LED driver
Plug & Play On Downlight Head Unit
Supplied With 3-Pole Connector Block For Easy Install



GENERAL INFORMATION	
Product Code	NWP/FO/DRIVER/12/CB3P
Product Range	Downlights
Product Category	Downlights
IP Rating	20
IK Rating	N/A
Warranty	7 Years
DIMENSION/WEIGHT	
Dimensions Circular (DIA x H) (mm)	DIA=N/A, H=N/A
Dimensions Square/Rectangular (L x W x H) (mm)	L=0, W=0, H=0
Cut-out Size (mm)	N/A
Product Weight (Kg)	0.16
CONSTRUCTION	
Body Material	N/A
Body Colour	N/A
Optical Material	N/A
Optical Finish	N/A
Termination	3x2x2.5mm sq. Push In Terminal
Driver - Intergal or Remote	Remote
PACKAGING	
Carton Dimensions (mm)	208x35x91
Quantity per Outer Carton	N/A
Total Weight inc. Carton (Kg)	0.19

LUMINAIRE PERFORMANCE	
Energy Rating	N/A
Luminaire Lumens (lm)	N/A
Power Consumption (W)	See head unit
LED Lumens (lm/W)	N/A
Efficacy (l.lm/c.W)	See head unit
Operating Temp. (Min/Max)	-20°C to 25°C
LIGHT SOURCE	
Type	N/A
Correlated Colour Temp.	N/A
Colour Rendering Index (CRI)	N/A
Lumen Depreciation	N/A
SDCM	N/A
ELECTRICAL INPUT	
VOLTAGE (V)	220-240V AC
Operating Frequency	50
In Rush	16A @ 100us
Drivers per MCB*	B10=32 B16=50 C10=40 C16=60
Class	Class 2
Power Factor	>0.95
Cable Entry	N/A
ELECTRICAL OUTPUT	
Forward Current (mA)	350mA
Forward Voltage (Vf)	N/A
EMERGENCY DATA	
Mode of Operation	N/A
Battery Duration	N/A
Battery Type	N/A
Battery Specification	N/A
Ballast Lumen Factor (BLF)	N/A
DIMMING	
DALI	N/A
OTHER	N/A
Switch Dim	N/A
Corridor Function	N/A
SENSORS	
Microwave	N/A
PIR	N/A
STANDARDS/APPROVALS	
CE Marked	Yes
Certificate of Conformity	Yes
Accreditations	N/A
BARCODE	
EAN NUMBER	5055943072916
E NUMBER	7982175

* GUIDE ONLY

