



## LED Soft Tube T300

LED bulb, clear, E27, PHASE, 9W, 1900K

The flexible LED filaments look confusingly similar to filaments and, with their warm, glare-free light, are ideal for decorative lighting purposes. They are fully dimmable and, with the new filament styles, are a real eye-catcher even before they are switched on.

## **TECHNICAL DATA**

Socket         E27           IP Code         IP20           Dimmable         Yes           Dimming technology         trailing edge           Electrical power factor         0.8           Wattage         8 W           Starting time         0.5 s           Start time         0 s           Lumen         400 lm           Colour temperature         1900 Kelvin           Color         transparent           CRI         90           Service life         20000 h           Switching cycles         100000           Risk Group         0           Length         30 cm           Diameter         3.2 cm	Item no.	1008374
DimmableYesDimming technologytrailing edgeElectrical power factor0.8Wattage8 WStarting time0.5 sStart time0 sLumen400 lmColour temperature1900 KelvinColortransparentCRI90Service life20000 hSwitching cycles100000Risk Group0Length30 cm	Socket	E27
Dimming technology trailing edge  Electrical power factor 0.8  Wattage 8 W  Starting time 0.5 s  Start time 0 s  Lumen 400 lm  Colour temperature 1900 Kelvin  Color transparent  CRI 90  Service life 20000 h  Switching cycles 100000  Risk Group 0  Length 30 cm	IP Code	IP20
Electrical power factor         0.8           Wattage         8 W           Starting time         0.5 s           Start time         0 s           Lumen         400 lm           Colour temperature         1900 Kelvin           Color         transparent           CRI         90           Service life         20000 h           Switching cycles         100000           Risk Group         0           Length         30 cm	Dimmable	Yes
Wattage         8 W           Starting time         0.5 s           Start time         0 s           Lumen         400 lm           Colour temperature         1900 Kelvin           Color         transparent           CRI         90           Service life         20000 h           Switching cycles         100000           Risk Group         0           Length         30 cm	Dimming technology	trailing edge
Starting time         0.5 s           Start time         0 s           Lumen         400 lm           Colour temperature         1900 Kelvin           Color         transparent           CRI         90           Service life         20000 h           Switching cycles         100000           Risk Group         0           Length         30 cm	Electrical power factor	0.8
Start time         0 s           Lumen         400 lm           Colour temperature         1900 Kelvin           Color         transparent           CRI         90           Service life         20000 h           Switching cycles         100000           Risk Group         0           Length         30 cm	Wattage	8 W
Lumen         400 lm           Colour temperature         1900 Kelvin           Color         transparent           CRI         90           Service life         20000 h           Switching cycles         100000           Risk Group         0           Length         30 cm	Starting time	0.5 s
Colour temperature1900 KelvinColortransparentCRI90Service life20000 hSwitching cycles100000Risk Group0Length30 cm	Start time	0 s
Color         transparent           CRI         90           Service life         20000 h           Switching cycles         100000           Risk Group         0           Length         30 cm	Lumen	400 lm
CRI         90           Service life         20000 h           Switching cycles         100000           Risk Group         0           Length         30 cm	Colour temperature	1900 Kelvin
Service life 20000 h  Switching cycles 100000  Risk Group 0  Length 30 cm	Color	transparent
Switching cycles 100000  Risk Group 0  Length 30 cm	CRI	90
Risk Group 0 Length 30 cm	Service life	20000 h
Length 30 cm	Switching cycles	100000
- 3	Risk Group	0
Diameter 3.2 cm	Length	30 cm
	Diameter	3.2 cm
Net weight 0.09 kg	Net weight	0.09 kg
Gross weight 0.17 kg	Gross weight	0.17 kg