

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Dansani

Supplier's address: Dansani, Finlandsvej 8, 6100 Haderslev, DK

Model identifier: 190303792 LED - 06.2022

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	No cap-type		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters


Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	6	Energy efficiency class	E
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	632 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 234
On-mode power (P_{on}), expressed in W	5,2	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	97
Outer dimensions without separate control gear, lighting control	Height	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width		
	Depth		

parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,416 0,386	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	97	Survival factor	0,90	
the lumen maintenance factor	0,96			

(a) : not applicable;

(b) : not applicable;

Spectrum Test Report



Color Parameters:

Chromaticity Coordinate: $x=0.4159$ $y=0.3858$ $u'=0.2447$ $v'=0.5108$

CCT=3234K(Duv=-0.0043) Dominant WL:Ld =583.7nm Purity=40.6%

Ratio:R=23.8% G=72.9% B=3.3% Peak WL:Lp=636.3nm FWHM=180.3nm

Render Index:Ra=97.5

R1 =99 R2 =99 R3 =95 R4 =97 R5 =99 R6 =96 R7 =97

R8 =98 R9 =97 R10=95 R11=95 R12=81 R13=99 R14=96 R15=99

Photo Parameters:

Flux = 632.4 lm Eff. : 121.09 lm/W Fe = 2.393 W

Electrical parameters:


V = 14.926 V I = 0.3499 A P = 5.223 W PF = 1.000

LEVEL:OUT WHITE:ANSI_3500K

Status: Integral T = 1285 ms Ip = 51275 (78%)

Model:LPP-060AM-3150K-LED(35PCS) Number:3
Tester:ZW Date:2022-03-08
Temperature:25.3Deg Humidity:65.0%
Manufacturer:GB Remarks:SE001656

Model placed on the Union market from 01/06/2022



EPREL registration number: 1308389

<https://eprel.ec.europa.eu/qr/1308389>

Supplier: Dansani A/S (Manufacturer)

Website:

Customer care service:

Name: Dansani

Website: www.dansani.dk

Email: sba@dansani.dk

Phone: +4523829794

Address:

Finlandsvej 8
6100 Haderslev
Denmark