



<b>Category</b>	Bulkheads
<b>Application</b>	Ancillary, Commercial, Education, Healthcare, Hospitality, Outdoor, Retail
<b>Specification</b>	Architectural

# Mercurial

Mercurial 2 IP54 2CCT White DALI Self-Test Emergency

Code: AMER2/1/W/DD3/SM3



## PRODUCT FEATURES

- Utility LED wall/ceiling luminaire suitable for education and commercial applications and ancillary areas
- Corridor function options available for effective reduction in energy consumption
- Clip in gear tray ensures quick installation
- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 outputs, in one luminaire (AMER1/1/\*\* only)
- Side conduit entry covers retain sleek appearance when not in use

### GENERAL INFORMATION

<b>Wattage</b>	23W/34W
<b>Lumens Delivered</b>	3200 - 4700lm (4000K)
<b>Lm/W</b>	140lm/W (4000K)
<b>Beam Angle</b>	120
<b>CRI</b>	80
<b>CCT</b>	3000/4000K
<b>Input</b>	220-240V
<b>Operating Temp</b>	5°C - 40°C
<b>SDCM</b>	3
<b>Product Weight without Packaging</b>	2.12 kg

### TECHNICAL INFORMATION

<b>Light Source</b>	LED
<b>Colour / Finish</b>	White
<b>IP Rating</b>	IP54
<b>IK Rating</b>	IK08
<b>Class Protection</b>	2
<b>Internal / External</b>	Internal
<b>Surface / Recessed / Suspended</b>	Ceiling, Wall
<b>Lumen Depreciation</b>	L70 80,000h
<b>Warranty (Years)</b>	7
<b>CE Mark</b>	Yes
<b>Diameter</b>	500 mm
<b>Emergency Output Duration</b>	3 Hr





<b>Category</b>	Bulkheads
<b>Application</b>	Ancillary, Commercial, Education, Healthcare, Hospitality, Outdoor, Retail
<b>Specification</b>	Architectural

# Mercurial

Mercurial 2 IP54 2CCT White DALI Self-Test Emergency  
Code: AMER2/1/W/DD3/SM3

