



Category	Bulkheads
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Outdoor, Retail
Specification	Architectural

Mercurial

Mercurial 2 IP54 2CCT White Microwave Sensor DALI-Emergency

Code: AMER2/1/W/MWS/DM3



PRODUCT FEATURES

- Utility LED wall/ceiling luminaire suitable for education and commercial applications and ancillary areas
- Corridor function options available for effective reduction in energy consumption
- Clip in gear tray ensures quick installation
- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 outputs, in one luminaire (AMER1/1/** only)
- Side conduit entry covers retain sleek appearance when not in use

GENERAL INFORMATION

Wattage	23W/34W
Lumens Delivered	3200 - 4700lm (4000K)
Lm/W	140lm/W (4000K)
Beam Angle	120
CRI	80
CCT	3000/4000K
Input	220-240V
Operating Temp	5°C - 40°C
SDCM	3

TECHNICAL INFORMATION

Light Source	LED
Colour / Finish	White
IP Rating	IP54
IK Rating	IK08
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Ceiling, Wall
Lumen Depreciation	L70 80,000h
Warranty (Years)	7
CE Mark	Yes
Diameter	500 mm
Emergency Output Duration	3 Hr



Category	Bulkheads
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Outdoor, Retail
Specification	Architectural

Mercurial

Mercurial 2 IP54 2CCT White Microwave Sensor DALI-Emergency
Code: AMER2/1/W/MWS/DM3

