



|                      |  |
|----------------------|--|
| <b>Category</b>      | Bulkheads  |
| <b>Application</b>   | Ancillary, Commercial, Education, Healthcare, Hospitality, Outdoor, Retail |
| <b>Specification</b> | Architectural  |

# Mercurial

Mercurial 2 IP54 2CCT Silver Corridor Function Self-Test Emergency

Code: AMER2/1/S/CF/SM3



## PRODUCT FEATURES

- Utility LED wall/ceiling luminaire suitable for education and commercial applications and ancillary areas
- Corridor function options available for effective reduction in energy consumption
- Clip in gear tray ensures quick installation
- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 outputs, in one luminaire (AMER1/1/\*\* only)
- Side conduit entry covers retain sleek appearance when not in use

### GENERAL INFORMATION

|   |                       |
|---|-----------------------|
| <b>Wattage</b>                          | 23W/34W               |
| <b>Lumens Delivered</b>                 | 3200 - 4700lm (4000K) |
| <b>Lm/W</b>                             | 140lm/W (4000K)       |
| <b>Beam Angle</b>                       | 120                   |
| <b>CRI</b>                              | 80                    |
| <b>CCT</b>                              | 3000/4000K            |
| <b>Input</b>                            | 220-240V              |
| <b>Operating Temp</b>                   | 5°C - 40°C            |
| <b>SDCM</b>                             | 3                     |
| <b>Product Weight without Packaging</b> | 2.73 kg               |

### TECHNICAL INFORMATION

|                                       |               |
|---------------------------------------|---------------|
| <b>Light Source</b>                   | LED           |
| <b>Colour / Finish</b>                | Silver        |
| <b>IP Rating</b>                      | IP54          |
| <b>IK Rating</b>                      | IK08          |
| <b>Class Protection</b>               | 2             |
| <b>Internal / External</b>            | Internal      |
| <b>Surface / Recessed / Suspended</b> | Ceiling, Wall |
| <b>Lumen Depreciation</b>             | L70 80,000h   |
| <b>Warranty (Years)</b>               | 7             |
| <b>CE Mark</b>                        | Yes           |
| <b>Diameter</b>                       | 500 mm        |
| <b>Emergency Output Duration</b>      | 3 Hr          |



|                      |  |
|----------------------|--|
| <b>Category</b>      | Bulkheads  |
| <b>Application</b>   | Ancillary, Commercial, Education, Healthcare, Hospitality, Outdoor, Retail |
| <b>Specification</b> | Architectural  |

# Mercurial

Mercurial 2 IP54 2CCT Silver Corridor Function Self-Test Emergency  
Code: AMER2/1/S/CF/SM3

