



<b>Category</b>	Bulkheads
<b>Application</b>	Ancillary, Commercial, Education, Healthcare, Hospitality, Residential, Retail
<b>Specification</b>	Performance

# Disco EVO

Disco EVO 2 Self-Test Emergency  
Code: ADIS2/1/SM3

### Reinforced Base

Reinforced base with a pre-drilled back entry and grommet for enhanced durability and effortless installation



### Fast and Easy Install

Twist-on diffuser and 2-part design with push-fit terminals allow quick and easy installation



### Speed-Optimised Packaging

Packed with the base facing up and detached for a fast, hassle-free installation



## PRODUCT FEATURES

- Slim and modern bulkhead suitable for residential, commercial and industrial applications as well as ancillary areas
- All polycarbonate construction with opal diffuser and white trim ring with optional chrome, satin chrome or graphite trim ring accessories
- Gear tray located on the bezel, allowing the base to be installed and then the bezel connected, this coupled with 4x 20mm conduit entry points on base ensure a quick and simple installation
- Instant light output and unlimited switching
- High efficiency up to 145lm/W
- CCT selectable between 3000K, 4000K and 6500K and power selectable; offering a choice of 3 outputs, in one luminaire
- Two options of microwave sensor emergency

### GENERAL INFORMATION

<b>Wattage</b>	10 - 18W
<b>Lumens Delivered</b>	(4000K) 9W: 1200lm 12W: 1800lm 16W: 2300lm
<b>Lm/W</b>	(4000K) 9W: 135lm/W 12W: 145lm/W 16W: 145lm/W
<b>Beam Angle</b>	110
<b>CRI</b>	80
<b>CCT</b>	3000/4000/6500K
<b>Input</b>	220-240V
<b>Operating Temp</b>	0°C - 40°C
<b>SDCM</b>	5
<b>UGR</b>	26
<b>Product Weight without Packaging</b>	1.04 kg

### TECHNICAL INFORMATION

<b>Light Source</b>	LED
<b>Colour / Finish</b>	White
<b>IP Rating</b>	IP65
<b>IK Rating</b>	IK08
<b>Class Protection</b>	2
<b>Internal / External</b>	Internal / External
<b>Surface / Recessed / Suspended</b>	Ceiling, Wall
<b>Lumen Depreciation</b>	L70 54,000h
<b>Warranty (Years)</b>	5
<b>CE Mark</b>	Yes
<b>Diameter</b>	325 mm
<b>Height</b>	85 mm
<b>Emergency Output Duration</b>	3 Hr





<b>Category</b>	Bulkheads
<b>Application</b>	Ancillary, Commercial, Education, Healthcare, Hospitality, Residential, Retail
<b>Specification</b>	Performance

# Disco EVO

Disco EVO 2 Self-Test Emergency  
Code: ADIS2/1/SM3

