



Category	LED Strip
Application	Hospitality, Residential, Retail
Specification	Architectural

D-Cell Dim-to-Warm LED Strip

D-Cell 24V 9.6W IP67 Dim-to-Warm 5m

Code: D/24/02/67/06/00/S01/01



PRODUCT FEATURES

- D-CELL dim to warm LED strip suitable for residential and hospitality applications
- Fast fit plug and play connections remove the need for time consuming soldering of joints
- Joint and connection accessories sold separately
- Warm 3000K - 1800K provides great versatility, offering a multi-use solution with one product. The 3000K colour temperature can be utilised for task lighting, but when dimmed and changed to 1800K, the output serves to create a more relaxed and intimate light setting
- Multiple connector packs offer great time saving and ease when working on a large scale project
- 224

GENERAL INFORMATION

Wattage	9.6W/m
Lumens Delivered	960lm/m
Lm/W	95lm/W
Beam Angle	120
CRI	90
CCT	1800-3000K
Input	24V
Operating Temp	-20°C - 45°C
SDCM	3
Product Weight without Packaging	0.25 kg

TECHNICAL INFORMATION

Light Source	LED
IP Rating	IP67
Class Protection	3
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling, Recessed, Wall
Lumen Depreciation	L70 50,000h
Warranty (Years)	5
CE Mark	Yes
Height	4 mm
LED Strip LEDs Per Metre	224



Category	LED Strip
Application	Hospitality, Residential, Retail
Specification	Architectural

D-Cell Dim-to-Warm LED Strip

D-Cell 24V 9.6W IP67 Dim-to-Warm 5m

Code: D/24/02/67/06/00/S01/01