



Application	Hospitality, Residential, Retail
Specification	Architectural

P-Cell PRO LED Strip

P-Cell 24V 14.4W IP20 White 2700K 5m Code: P/24/04/20/01/27/S01/01







PRODUCT FEATURES

- P-CELL Professional LED strip suitable for high end residential, hospitality. retail and commercial applications
- Elite level LED chip technology with >97 CRI and low SDCM produce the best quality white light
- An extensive range of colour temperature options, IP ratings and power outputs offer the ultimate package of flexibility and versatility, suited for all high end applications
- Large strip pack sizes and multiple connector packs offers great time saving and ease when working on a large scale project

	GENERAL INFORMATION
Wattage	14.4W/m
Lumens Delivered	1468lm/m
Lm/W	102lm/W
Beam Angle	120
CRI	97
ССТ	2700K
Input	24V
Operating Temp	-20°C - 45°C
SDCM	3
Product Weight without Packagir	ng 0.07 kg

- Super high efficacy ensures peak performance, whilst also remaining economical and energy saving, helping to reduce overall energy consumption for all large scale installations
- High LED density (240 LEDs per metre) provides a uniform output reducing spotting and providing a more seamless output of light compared to traditional LED strips, coupled with a high CRI this ensures suitability for use within professional display and high end retail environments
- Fast fit plug and play connections available
- · Joint and connection accessories sold separately
- 240

IP Rating IP20 Class Protection 3 Internal / External Internal Surface / Recessed / Suspended Ceiling, Recessed, Wall Lumen Depreciation L70 50,000h Warranty (Years) 5 CE Mark Yes Height 2 mm	TECHNICAL INFORMATION		
Class Protection 3 Internal / External Internal Surface / Recessed / Suspended Ceiling, Recessed, Wall Lumen Depreciation L70 50,000h Warranty (Years) 5 CE Mark Yes Height 2 mm	Light Source	LED	
Internal / External Internal Surface / Recessed / Suspended Ceiling, Recessed, Wall Lumen Depreciation L70 50,000h Warranty (Years) 5 CE Mark Yes Height 2 mm	IP Rating	IP20	
Surface / Recessed / Suspended Ceiling, Recessed, Wall Lumen Depreciation L70 50,000h Warranty (Years) 5 CE Mark Yes Height 2 mm	Class Protection	3	
Lumen Depreciation L70 50,000h Warranty (Years) 5 CE Mark Yes Height 2 mm	Internal / External	Internal	
Warranty (Years)5CE MarkYesHeight2 mm	Surface / Recessed / Suspended	Ceiling, Recessed, Wall	
CE Mark Yes Height 2 mm	Lumen Depreciation	L70 50,000h	
Height 2 mm	Warranty (Years)	5	
-	CE Mark	Yes	
LED Strip LEDs Per Metre 240	Height	2 mm	
	LED Strip LEDs Per Metre	240	

ansell_lightingAnsell Lighting







Application	Hospitality, Residential, Retail
Specification	Architectural

P-Cell PRO LED Strip

P-Cell 24V 14.4W IP20 White 2700K 5m Code: P/24/04/20/01/27/S01/01

ACCESSORIES	
AOCTOW/12-24V/DIM	OCTO WiZ Connected 12-24V Dimmable Controller
AOCTO/RGBW/BTC	OCTO Indoor CCT/RGBW Controller 12-24V



