




Application	Hospitality, Residential, Retail	
Specification	Architectural	

P-Cell PRO LED Strip

P-Cell 24V 19.2W IP20 White 3000K 5m Code: P/24/05/20/01/30/S01/01







PRODUCT FEATURES

- P-CELL Professional LED strip suitable for high end residential, hospitality. retail and commercial applications
- Elite level LED chip technology with >97 CRI and low SDCM produce the best quality white light
- An extensive range of colour temperature options, IP ratings and power outputs offer the ultimate package of flexibility and versatility, suited for all high end applications
- Large strip pack sizes and multiple connector packs offers great time saving and ease when working on a large scale project
- Super high efficacy ensures peak performance, whilst also remaining economical and energy saving, helping to reduce overall energy consumption for all large scale installations
- High LED density (240 LEDs per metre) provides a uniform output reducing spotting and providing a more seamless output of light compared to traditional LED strips, coupled with a high CRI this ensures suitability for use within professional display and high end retail environments
- Fast fit plug and play connections available
- · Joint and connection accessories sold separately
- 240

Wattage 19.2W/m Lumens Delivered 1977Im/m Lm/W 103Im/W Beam Angle 120 CRI 97 CCT 3000K Input 24V Operating Temp -20°C - 45°C SDCM 3	GENE	ral information	
Lm/W 103Im/W Beam Angle 120 CRI 97 CCT 3000K Input 24V Operating Temp -20°C - 45°C	Wattage	19.2W/m	
Beam Angle 120 CRI 97 CCT 3000K Input 24V Operating Temp -20°C - 45°C	Lumens Delivered	1977lm/m	
CRI 97 CCT 3000K Input 24V Operating Temp -20°C - 45°C	Lm/W	103lm/W	
CCT 3000K Input 24V Operating Temp -20°C - 45°C	Beam Angle	120	
Input 24V Operating Temp -20°C - 45°C	CRI	97	
Operating Temp -20°C - 45°C	CCT	3000K	
	Input	24V	
SDCM 3	Operating Temp	-20°C - 45°C	
	SDCM	3	
Product Weight without Packaging 0.07 kg	Product Weight without Packaging	0.07 kg	

TECHNICAL INFORMATION		
Light Source	LED	
IP Rating	IP20	
Class Protection	3	
Internal / External	Internal	
Surface / Recessed / Suspended	Ceiling, Recessed, Wall	
Lumen Depreciation	L70 50,000h	
Warranty (Years)	5	
CE Mark	Yes	
Height	2 mm	
LED Strip LEDs Per Metre	240	









Application	Hospitality, Residential, Retail	
Specification	Architectural	

P-Cell PRO LED Strip

P-Cell 24V 19.2W IP20 White 3000K 5m Code: P/24/05/20/01/30/S01/01

ACCESSORIES		
AOCTOW/12-24V/DIM	OCTO WiZ Connected 12-24V Dimmable Controller	
AOCTO/RGBW/BTC	OCTO Indoor CCT/RGBW Controller 12-24V	





