

NVC UK - NVC Lighting Limited
NVC Park 201, Hollymoor Way, Rubery,
Birmingham, B31 5HE
T +44 (0)121 457 6340
E sales@nvcuk.com

NVC NORDICS - NVC Lighting AB
Albybergsringen 3b 137 69 Österhaninge
T +46(0)8 735 55 40
Sweden info@nvc-lighting.se



DATASHEET

TORONTO

Toronto 38-60W 5Ft M3 Lithium 830-840-860

Energy Efficiency Classification Class
Strong PC Enclosure & Stainless Steel Clips
5-Pole Through Wired



GENERAL INFORMATION	
Product Code	NTT/5/38-60/M3L/830-40-60
Product Range	Industrial
Product Category	Industrial
IP Rating	65
IK Rating	IK10
Warranty	5 Years Unlimited
DIMENSION/WEIGHT	
Dimensions Circular (DIA x H) (mm)	DIA=N/A, H=N/A
Dimensions Square/Rectangular (L x W x H) (mm)	L=1500, W=113, H=75
Cut-out Size (mm)	N/A
Product Weight (Kg)	N/A
CONSTRUCTION	
Body Material	PC
Body Colour	White
Optical Material	PC
Optical Finish	N/A
Termination	5x2x2.5mm sq. Push In Terminal
Driver - Intergal or Remote	Integral
PACKAGING	
Carton Dimensions (mm)	N/A
Quantity per Outer Carton	N/A
Total Weight inclc. Carton (Kg)	N/A

LUMINAIRE PERFORMANCE	
Energy Rating	C
Luminaire Lumens (lm)	5793 / 5957 / 6171 (38W) 9159 / 9532 / 9771 (60W)
Power Consumption (W)	27 / 37
LED Lumens (lm/W)	N/A
Efficacy (l.lm/c.W)	150 / 157 / 161 (38W) 150 / 160 / 161 (60W)
Operating Temp. (Min/Max)	-20°C to 25°C
LIGHT SOURCE	
Type	LED
Correlated Colour Temp.	4000
Colour Rendering Index (CRI)	>80
Lumen Depreciation	L80 100000
SDCM	<3
ELECTRICAL INPUT	
VOLTAGE (V)	220-240V AC
Operating Frequency	50/60
In Rush	<25A
Drivers per MCB*	B10=16 B16=28 C10= 16 C16=28
Class	Class 1
Power Factor	>0.95
Cable Entry	Ends
ELECTRICAL OUTPUT	
Forward Current (mA)	-
Forward Voltage (Vf)	N/A
EMERGENCY DATA	
Mode of Operation	N/A
Battery Duration	3 Hours
Battery Type	LiFePO4
Battery Specification	3.2V, 3Ah
Emergency Lumens	N/A
DIMMING	
DALI	N/A
OTHER	N/A
Switch Dim	N/A
Corridor Function	N/A
SENSORS	
Microwave	N/A
PIR	N/A
STANDARDS/APPROVALS	
CE Marked	Yes
Certificate of Conformity	Yes
Accreditations	N/A
BARCODE	
EAN NUMBER	N/A

* GUIDE ONLY

