

NVC UK - NVC Lighting Limited
NVC Park 201, Hollymoor Way, Rubery,
Birmingham, B31 5HE
T +44 (0)121 457 6340
E sales@nvcuk.com

NVC NORDICS - NVC Lighting AB
Albybergsringen 3b 137 69 Österhaninge
T +46(0)8 735 55 40
Sweden info@nvc-lighting.se
Finland info@nvc-lighting.fi
Denmark info@nvc-lighting.dk



DATASHEET

BROADWAY

Broadway 50W LED Linear White OP1 840

Lighting for the data hall; dual asymmetric optics, Tamb 50C
DALI or wireless control options
Components accessed from front of fitting for easy maintenance



GENERAL INFORMATION	
Product Code	NBW/50/WH/OP1/840
Product Range	Track
Product Category	Track
IP Rating	20
IK Rating	N/A
Warranty	N/A
DIMENSION/WEIGHT	
Dimensions Circular (DIA x H) (mm)	DIA=N/A, H=N/A
Dimensions Square/Rectangular (L x W x H) (mm)	L=1850, W=47, H=32
Cut-out Size (mm)	N/A
Product Weight (Kg)	1.85
CONSTRUCTION	
Body Material	Steel
Body Colour	White
Optical Material	N/A
Optical Finish	N/A
Termination	Track adaptor
Driver - Intergal or Remote	Remote
PACKAGING	
Carton Dimensions (mm)	N/A
Quantity per Outer Carton	N/A
Total Weight incl. Carton (Kg)	N/A

LUMINAIRE PERFORMANCE	
Energy Rating	N/A
Luminaire Lumens (lm)	7375
Power Consumption (W)	50
LED Lumens (lm/W)	N/A
Efficacy (l.lm/c.W)	147
Operating Temp. (Min/Max)	-20°C to 45°C
LIGHT SOURCE	
Type	LED
Correlated Colour Temp.	4000
Colour Rendering Index (CRI)	>85
Lumen Depreciation	L80 >78000 hours (as per TM21)
SDCM	<3
ELECTRICAL INPUT	
VOLTAGE (V)	220-240V AC
Operating Frequency	50
In Rush	N/A
Drivers per MCB*	B10 =14, B13 =19, B16 =23
Class	Class 1
Power Factor	0.94
Cable Entry	N/A
ELECTRICAL OUTPUT	
Forward Current (mA)	500
Forward Voltage (Vf)	N/A
EMERGENCY DATA	
Mode of Operation	Self Test or DALI
Battery Duration	N/A
Battery Type	N/A
Battery Specification	N/A
Emergency Lumens	N/A
DIMMING	
DALI	N/A
OTHER	N/A
Switch Dim	N/A
Corridor Function	N/A
SENSORS	
Microwave	N/A
PIR	Option
STANDARDS/APPROVALS	
CE Marked	Yes
Certificate of Conformity	Yes
Accreditations	N/A
BARCODE	
EAN NUMBER	N/A

* GUIDE ONLY

