

## DATASHEET

### TULSA V4

Tulsa V4 Mains Dimmable Driver 28W 600x600 Panel Plug and Lead

28W Fixed Output LED Driver For Panels  
Plug & Play On Panel  
2m Lead With 2-Pin Euro Plug For Direct Connection



| GENERAL INFORMATION                            |                     |
|------------------------------------------------|---------------------|
| Product Code                                   | NTU/MD/DRV/28/66/PL |
| Product Range                                  | LED Panels          |
| Product Category                               | LED Panels          |
| IP Rating                                      | 20                  |
| IK Rating                                      | N/A                 |
| Warranty                                       | 7 Years             |
| DIMENSION/WEIGHT                               |                     |
| Dimensions Circular (DIA x H) (mm)             | DIA=N/A, H=N/A      |
| Dimensions Square/Rectangular (L x W x H) (mm) | L=0, W=0, H=N/A     |
| Cut-out Size (mm)                              | N/A                 |
| Product Weight (Kg)                            | 0.3                 |
| CONSTRUCTION                                   |                     |
| Body Material                                  | N/A                 |
| Body Colour                                    | N/A                 |
| Optical Material                               | N/A                 |
| Optical Finish                                 | N/A                 |
| Termination                                    | Euro plug           |
| Driver - Intergal or Remote                    | Remote              |
| PACKAGING                                      |                     |
| Carton Dimensions (mm)                         | N/A                 |
| Quantity per Outer Carton                      | N/A                 |
| Total Weight incl. Carton (Kg)                 | N/A                 |

| LUMINAIRE PERFORMANCE        |                             |
|------------------------------|-----------------------------|
| Energy Rating                | N/A                         |
| Luminaire Lumens (lm)        | N/A                         |
| Power Consumption (W)        | See panel                   |
| LED Lumens (lm/W)            | N/A                         |
| Efficacy (l.lm/c.W)          | See panel                   |
| Operating Temp. (Min/Max)    | -20°C to 25°C               |
| LIGHT SOURCE                 |                             |
| Type                         | N/A                         |
| Correlated Colour Temp.      | N/A                         |
| Colour Rendering Index (CRI) | N/A                         |
| Lumen Depreciation           | N/A                         |
| SDCM                         | N/A                         |
| ELECTRICAL INPUT             |                             |
| VOLTAGE (V)                  | 220-240V AC                 |
| Operating Frequency          | 50                          |
| In Rush                      | <25A                        |
| Drivers per MCB*             | B10=16 B16=28 C10=25 C16=42 |
| Class                        | Class 2                     |
| Power Factor                 | >0.95                       |
| Cable Entry                  | N/A                         |
| ELECTRICAL OUTPUT            |                             |
| Forward Current (mA)         | N/A                         |
| Forward Voltage (Vf)         | N/A                         |
| EMERGENCY DATA               |                             |
| Mode of Operation            | N/A                         |
| Battery Duration             | N/A                         |
| Battery Type                 | N/A                         |
| Battery Specification        | N/A                         |
| Emergency Lumens             | N/A                         |
| DIMMING                      |                             |
| DALI                         | N/A                         |
| OTHER                        | N/A                         |
| Switch Dim                   | N/A                         |
| Corridor Function            | N/A                         |
| SENSORS                      |                             |
| Microwave                    | N/A                         |
| PIR                          | N/A                         |
| STANDARDS/APPROVALS          |                             |
| CE Marked                    | Yes                         |
| Certificate of Conformity    | Yes                         |
| Accreditations               | N/A                         |
| BARCODE                      |                             |
| EAN NUMBER                   | 5056673224514               |
| E NUMBER                     | 7982623                     |

\* GUIDE ONLY

