



Application	Commercial, Industrial, Retail
Specification	Performance

Aztec

Aztec 2 80W Asymmetric Floodlight
Code: AAZT2/ASY/1



PRODUCT FEATURES

- High performance die-cast aluminium LED floodlight suitable for industrial, commercial and coastal applications
- High output, high efficiency asymmetric lens technology for anti-light pollution (asymmetric versions only)
- Integral photocell with 2 x lux settings and (deleted 'on-') off options
- 10KV surge protection on 120W to 320W, 6KV surge protection on 20W to 80W
- Marine grade construction ideal for coastal and adverse weather, swimming pool and chemical plant applications
- CCT selectable between 3000K, 4000K and 5000K
- Fast fit lever terminals ensure easy and speedy loop-in, loop installation
- Pre-installed breathable gland prevents internal moisture accumulation

GENERAL INFORMATION

Wattage	80W
Lumens Delivered	14000lm (4000K)
Lm/W	175lm/W
Beam Angle	60/120
CRI	70
CCT	3000/4000/5000
Input	220-240V
Operating Temp	-30°C - 50°C
SDCM	5
UGR	31
Product Weight without Packaging	3.1 kg

TECHNICAL INFORMATION

Light Source	LED
Colour / Finish	Black
IP Rating	IP66
IK Rating	IK08
Class Protection	1
Internal / External	External
Surface / Recessed / Suspended	Surface
Lumen Depreciation	L80 100,000h
Warranty (Years)	7
CE Mark	Yes
Height	63 mm



Application	Commercial, Industrial, Retail
Specification	Performance

Aztec

Aztec 2 80W Asymmetric Floodlight
Code: AAZT2/ASY/1

