

## TONGIA


Material	steel pipes $\varnothing$ 20 mm / steel profiles 30 x 30 mm
Connection thread	4 x G1/2"
Testing overpressure	1,3 MPa
Max. operating overpressure	1,0 MPa
Max. operating temperature	110 °C
Number of pipes	15, 24, 32







TONGIA 1135 x 600

Type H/L [mm]	Depth B [mm]	Weight [kg]	Water capacity [l]	Temperature exponent [n]	Heating Output [W]			Recommended power input chrome [W]		Connection span [mm]
					75/65/20 °C	70/55/20 °C	55/45/20 °C			
695/500	30	5,7	2,6	1,230	324	265	173	300	200	470
695/600	30	6,6	3,0	1,230	380	311	203	400	300	570
1135/500	30	9,2	4,2	1,249	511	417	270	500	400	470
1135/600	30	10,6	4,8	1,249	599	489	316	600	500	570
1535/500	30	12,3	5,7	1,244	705	576	374	700	500	470
1535/600	30	14,1	6,4	1,244	826	675	438	800	600	570

Thermal power measuring follows in accordance with EN 442.  
 Chrome surface treatment reduces heating capacity by ~30%.  
 Accessories (page 48, 49 and 50) is not part of the radiator.



Connection options



	A [mm]	X [mm]
Plastic brackets (RAL 9006, 9016)	84-94	69-79
Metal brackets (Other colours)	88-98	73-83

DTON 0695 0500...  
DTON 0695 0600...

DTON 1135 0500...  
DTON 1135 0600...

DTON 1535 0500...  
DTON 1535 0600...