



MADE IN GERMANY



Product number 1182778502
EAN 4007123687473

DESCRIPTION

- According to EN 61316.
- Reel body made of special plastic on galvanised carrying frame.
- Innovative "cablepilot" carrying handle for perfect cable routing. Swings on both sides for easy carrying and hanging.
- With twist handle for convenient retraction.
- CEE plug 400 V/16 A,
- 1 CEE socket 400 V/16 A,
- 2 splash-proof 230 V protective contact sockets.
- Cable quality: RN cable, very robust and oil-resistant.
- RN cable is approved for difficult building conditions in accordance with VDE 0100 Part 704.
- Sockets with earthing contact distributed over separate phases.
- With 3-pole safety cut-out and overheating protection.
- With drum brake.
- Category 2 equipment (K2 DGVU 203-005): For use in harsh operating conditions with high mechanical, physical and chemical impacts.

TECHNICAL DATA

Cable quality	Rubber-Neoprene	Plug system socket	Type K (DK)
Cable length	20 m + 0 m	Plug system plug	CEE 16 A 3P+N+E (5p) 400 V
Cable designation	H07RN-F 5G2,5	Max. current carrying capacity	16 A
Cable colour	signal red	Nominal input voltage	230 V/400 V
Reel diameter	300 mm	Degree of protection (IP)	IP44
Plug system CEE socket	CEE 1x 16 A 3P+N+E (5p) 400 V		

PACKAGING, DIMENSIONS AND WEIGHTS

UP	1	Weight of product (including packaging)	7.77 kg
Weight of product (without packaging)	7.77 kg	Dimension LxWxH (incl. packing)	24.5 cm x 32 cm x 41 cm
Dimension LxWxH (without packing)	18.5 cm x 30 cm x 39.5 cm		