

A4652SK

Pre-insulated through connector for 4-6 mm² cable, made of Cu, tin plated, plastic PC. Used with certified tool GSA0760.



Item number	7289-500500
EAN	7393487101852
E-number (SE)	0813207
Snro (FI)	5204930
EI-number (DK)	2921613671
EI-number (NO)	2000536
Pieces per pack	50
Gross weight (kg)	0.003
Depth [TrPack] (mm)	122
Width [TrPack] (mm)	48
Height [TrPack] (mm)	310
Name	A4652SK
Brand	ELPRESS
ETIM-class	Crimp splices for copper conductor (EC001059)
Country of origin	CN
Customs statistical number (taric code)	85369010 - Connections < 1000 V
Basic UOM	PCS
Net weight (kg)	0.003
Height Pack (mm)	100
Depth Pack (mm)	60
Width Pack (mm)	46
Model	Normal version
Surface protection	Tin plated
Insulation	Fully isolated
Oil stop/centre bar	No
For pull protected connections	No
Colour insulation	Yellow
AWG-range, Min	12
AWG-range, Max	10
Nominal cross section, Min (mm ²)	4
Suitable for fine strand conductors	No
Suitable for flat conductors	No
Suitable for insulated varnish	No
Suitable for solid conductors	No
Suitable for stranded conductors	No
Suitable for round conductors	No
AWG/MCM Cu	12 - 10 AWG
mm ² Cu	4-6
d (mm)	6.5
D (mm)	8
L (mm)	27.5
s (mm) - strip length	7
Insulation material	PC
Tool	GSA0760
Weight (kg)	0.003

