



SVEN

136-1003s6h0

SVEN PD SUSPENSION made of metal, black, similar to RAL 9005, opal silicone diffuser cream, beam 130°, light output direct, with converter, max. 700mA, dimmability: not dimmable, cable black, adapter/ceiling base black, pendant length 3000mm, IP20




DRAWING



TECHNICAL DETAILS

System perform. [W]	15
Bulb type	LED
Luminous flux [lm]	1230
Current sec. [mA]	700
Colour temp. [K]	2700/3000K
CRI	>90
Optics	opal silicone diffuser
Designer	Rainer Mutsch
Converter	with converter
Dimming	not dimmable
Light output	direct
Beam angle [°]	130°
Voltage [V]	220-240V 50/60Hz
Material	metal
Length [mm]	280
Height [mm]	50
Pendant length [mm]	3000
Diameter [mm]	280
IP protection class	IP20
Voltage class	protection cl. II
Net weight [kg]	0,84
Colour lamp	black
RAL	9005
Colour of glass/shade	cream
Colour adapter/ceiling base	black
Electric wire	black
EAN-Number	9010506714470
Lifetime [h]	L80 B10 50 000
Energy efficiency cl.	D

LIGHT DISTRIBUTION CURVE



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.