

Dual Color LED Controller Kit

Model No.: A/KT/02/01/01

2 channels constant voltage/Touch color slide/Step-less dimming/Wireless remote 30m distance



FC CE RoHS (REACH) LVD RED

Features

- Ultra sensitive color adjustment touch slide
- Smooth dimming and switch without any flickering
- Auto-transmitting function: Controller automatically transmit signal to another controller with 30 m control distance
- Synchronize on multiple number of controllers
- Light on/ off fade time 3 s selectable
- Magnet on the back which can be easily stuck on back holder or any metal surfaces

Technical Parameters

LED Receiver's Input and Output	
Input voltage	1.2-2.4 VDC
Input current	10.5A
Output voltage	2x(1.2-2.4)VDC
Output current	2CH,5A/CH
Output power	2x(6.0-1.20)W
Output type	Constant voltage

Dimming data	
Dimming level	4096 levels
Dimming range	0 - 100 %
Dimming curve	Linear
PWM Frequency	2000Hz

Warranty and Protection	
Warranty	5 years
Protection	Reverse Polarity



LED Remote's Input and Output	
Output signal	RF (2.4 GHz)
Working voltage	3 VDC (CR2032)
Working current	< 5 mA
Standby current	< 10 μ A
Standby time	1 year
Remote distance	30 m

Safety and EMC	
EMC standard (EMC)	ETSI EN 301 489-1 V2.2.3 ETSI EN 301 489-17 V3.2.4
Safety standard(IVD)	EN 62368-1:2020+A11:2020
Radio Equipment(RED)	ETSI EN 300 328 V2.2.2
Certification	CE,EMC, LVD,RED

Environment	
Operation temperature	Ta: -30 °C ~ +55 °C
Case temperature(Max.)	Tc: +85 °C
IP rating	IP20

V2+R12 Dual Color LED Controller Kit

Mechanical Structures and Installations



Wiring Diagram

