

**E-Charge, cable type 2 - type 2, 3 phase, 16A, Spiral,  
3M/5M**

**DELTA**CO



- Weight: 2.3 kg
- Rating: IP66
- Spiral cable 3/5m
- Operating temperature: -30°C to +50°C
- Cable: EV07EE-H, 5G2.5mm<sup>2</sup> + 1x05mm<sup>2</sup>
- Protection against moisture, dirt, and dust during storage.

**The Deltaco e-Charge EV-3215-S charging cable is compatible with all vehicles equipped with a Type 2 socket for efficient charging via a public charger or your own dedicated home charging box with Type 2 socket using mode 3 charging. The cable is equipped with silver-plated connectors and has an output of up to 11 kW**

The cable is made from a TPE material that provides good resistance against oil, wear, and UV light. The cable remains flexible even in cold temperatures. Type 2 sockets are now the EU standard, used by car manufacturers such as AUDI, BMW, Hyundai, KIA, Mercedes, Porsche, Seat, Skoda, Tesla, Volkswagen, and Volvo. The charging of the car is monitored through a two-way communication between the car and the charger. When the cable is connected to the car, a self-test is conducted to ensure the cable is properly connected and the car is ready to receive power before the charging begins. The cable's connectors are mechanically locked in place when the cable is energized, providing protection against theft and unauthorized use during charging. After charging, unlock the car to release the mechanical lock and remove the charging cable from the car's side first to disconnect it from the charger.

## SPECIFICATIONS

<b>Color</b>	Black
<b>Cable type</b>	External power
<b>LSZH</b>	Yes
<b>Warranty</b>	3 years

## LOGISTIC

<b>Item number</b>	EV-3215-S
<b>Manufacturer part number</b>	EV-3215-S
<b>Country of origin</b>	China
<b>Sales unit bar code</b>	7333048057693
<b>Sales unit height</b>	80 mm
<b>Sales unit width</b>	400 mm
<b>Sales unit depth</b>	380 mm
<b>Sales unit gross weight</b>	2.50 kg
<b>Sales unit net weight</b>	2.30 kg
<b>Master carton height</b>	400 mm
<b>Master carton width</b>	420 mm
<b>Master carton depth</b>	430 mm
<b>Master carton weight</b>	12.50 kg
<b>Master carton quantity</b>	5