

VSG 36 LG

Stop end, polyamide, RAL 7035, Pg36



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



Material	Polyamide, fibre reinforced
Temp. range min	-40 °C
Temp. range max	100 °C
Protection class	IP56
Advice	with sealing IP66/IP68
Thread type	PG
Ø Connection thread D	36
Length screw-in thread L	10 mm
Total length TL	15 mm
External diameter ED	55 mm
Product Color	RAL 7035
Order no. RAL 7035	50060735
Type	VSG 36 LG
Packing unit	25
EAN number	4007685607353
Tariff number	39269097
ETIM-Classification	EC000032

Recommended accessories

MUG 36 LG	10060677
ADR 36	10061426

17.02.2026

Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com



Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com