

VSG 42 LG

Stop end, polyamide, RAL 7035, Pg42



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



Material	Polyamide, fibre reinforced
Temp. range min	-40 °C
Temp. range max	100 °C
Protection class	IP56
Advice	with sealing IP66/IP68
Thread type	PG
Ø Connection thread D	42
Length screw-in thread L	10 mm
Total length TL	16 mm
External diameter ED	62 mm
Product Color	RAL 7035
Order no. RAL 7035	50060736
Type	VSG 42 LG
Packing unit	25
EAN number	4007685607360
Tariff number	39269097
ETIM-Classification	EC000032

Recommended accessories

MUG 42 LG	10060678
ADR 42	10061427

17.02.2026

Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com



Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com