


MONDANA disc

312753.002.1.730 | Surface-mounted luminaires



Ceiling and wall luminaires
4068754036580
D 580, H 77

Ceiling mounting, Wall (surface)
traffic white, matt (RAL 9016)



Decorative round surface-mounted luminaire for indoor and outdoor use. Base and bezel ring made of UV-stabilized plastic (polycarbonate). Diffuser: plastic (non-yellowing polycarbonate), opal, impact resistant. Diffuser fastening: bayonet system. Homogeneous light distribution from the diffuser. Indirect light distribution for soft ceiling illumination. Suitable for Ceiling mounting, Pendel für schräge Decke, Wall (surface). Useful markings for alignment with the laser as well as support points for the spirit level. Very easy installation thanks to plug-and-play connector system. The large connection compartment on the back for convenient connections is also ideal for through wiring. Base fixing slots outside of gasketed area, drill hole deviations can be compensated. MultiColour: Colour temperature individually adjustable either 3000 K or 4000 K. With Casambi smart+free Bluetooth® control for wireless network and operation using Android / iOS devices, free app available for download. Pendant luminaire also possible with accessories. Luminaire with limited surface temperature in accordance with EN 60598-2-24 for use in environments where no unusual dust deposits are expected. Environmentally friendly and resource-saving due to replaceable and recyclable components.

Product specifications

Diameter D	580 mm
Height H	77 mm
Weight	2.95 kg
Light source	LED
Colour temperature	3000 K 4000 K
Rated luminous flux	3000 K: 5950 lm 4000 K: 6150 lm
System power	3000 K: 43 W 4000 K: 43 W
System efficiency	3000 K: 138 lm/W 4000 K: 143 lm/W
Glare evaluation RUG (4H 8H)	3000 K: 22,3 4000 K: 22,4
Beam angle	down 118° up 180°
LED rated life	100000h (L80/B50)
Colour rendering index (CRI)	80
Colour tolerance (McAdam)	3 SDCM
Photobiological safety according to EN 62471	Risk group 0
Driver	Converter, dimmable
Control	smart+free (Bluetooth)
Voltage	220 - 240 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	16
Luminaires on B16A fuse	26
Luminaires on C10A fuse	27
Luminaires on C16A fuse	44
Inrush current / Inrush current duration	15.6 A / 248 µs
CIE Flux Code / CEN Flux Code	44 75 93 90 100
Type of protection	IP 54
Protection class	II
Filament test	850 °C
Impact resistance	IK08
Ambient temperature	-20 °C to +35 °C

Safety marks	D-mark
Conformity mark	CE

Accessories



983416.002
Pendant kit. Pendant length 1500 mm.



983416.012
Pendant kit. Pendant length 3000 mm.



983411.002
Spacer



983523.000
Theft protection



983430.002
Bracket set for fabric lampshades.



983422.FC01
Chintz fabric lampshade, Shape: cylinder

Spareparts



983276.002
Replacement diffuser



983288.002
Replacement LED diffuser unit



983551.002
Cover ring