


MONDANA disc

312751.002.1 | Surface-mounted luminaires



Ceiling and wall luminaires
4068754036405
D 380, H 77

Ceiling mounting, Wall (surface)
traffic white, matt (RAL 9016)



Decorative round surface-mounted luminaire for indoor and outdoor use. Base and bezel ring made of UV-stabilized plastic (polycarbonate). Diffuser: plastic (non-yellowing polycarbonate), opal, impact resistant. Diffuser fastening: bayonet system. Homogeneous light distribution from the diffuser. Indirect light distribution for soft ceiling illumination. Suitable for Ceiling mounting, Pendel für schräge Decke, Wall (surface). Useful markings for alignment with the laser as well as support points for the spirit level. Very easy installation thanks to plug-and-play connector system. The large connection compartment on the back for convenient connections is also ideal for through wiring. Base fixing slots outside of gasketed area, drill hole deviations can be compensated. MultiLumen: Multi-step adjustable luminous flux. Factory-set to maximum luminous flux. MultiColour: Colour temperature individually adjustable either 3000 K or 4000 K. Pendant luminaire also possible with accessories. Luminaire with limited surface temperature in accordance with EN 60598-2-24 for use in environments where no unusual dust deposits are expected. Environmentally friendly and resource-saving due to replaceable and recyclable components.

Product specifications

Diameter D	380 mm
Height H	77 mm
Weight	1.29 kg
Light source	LED
Colour temperature	3000 K 4000 K
Rated luminous flux	3000 K: 850 lm 2650 lm 4000 K: 900 lm 2800 lm
System power	3000 K: 6 W 19 W 4000 K: 6 W 19 W
System efficiency	3000 K: 142 lm/W 139 lm/W 4000 K: 150 lm/W 147 lm/W
Glare evaluation RUG (4H 8H)	3000 K: 18,4 22,3 4000 K: 18,6 22,5
Beam angle	down 126° up 180°
LED rated life	100000h (L80/B50)
Colour rendering index (CRI)	80
Colour tolerance (McAdam)	3 SDCM
Photobiological safety according to EN 62471	Risk group 0
Driver	Converter
Control	on/off
Voltage	220 - 240 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	41
Luminaires on B16A fuse	65
Luminaires on C10A fuse	68
Luminaires on C16A fuse	110
Inrush current / Inrush current duration	14 A / 130 µs
CIE Flux Code / CEN Flux Code	41 72 91 86 100
Type of protection	IP 54
Protection class	II
Filament test	850 °C
Impact resistance	IK08
Ambient temperature	-20 °C to +35 °C

Safety marks	D-mark
Conformity mark	CE

Accessories



983416.002
Pendant kit. Pendant length 1500 mm.



983416.012
Pendant kit. Pendant length 3000 mm.



983411.002
Spacer



983523.000
Theft protection



983430.002
Bracket set for fabric lampshades.



983420.FC01
Chintz fabric lampshade, Shape: cylinder

Spareparts



983272.002
Replacement diffuser



983284.002
Replacement LED diffuser unit



983549.002
Cover ring