

Technical datasheet: PVC - PVC

Type of isolation:	PVC T70°C, PVC T70°C
Working voltage:	300/300V
Regulation directives:	CE
In conformity with the the standard:	CEI 20-20/5 Ed. 1996 + V1:2002+V2:2002
Approval marks	IEMMEQU <HAR>



Code	Sections mm ²	Composi- tion (nxØ(mm))	Color	Cores colours	Shape	Dimension External Ø(mm)	Designation	Textile
418Axx07	2 x 0,75	24 x 0,20	White	B, M	Round	Ø5,8 ± 0,2 mm	H03VV-F	YES
418Axx08	2 x 0,75	24 x 0,20	Black	B, M	Round	Ø5,8 ± 0,2 mm	H03VV-F	YES
418Axx09	2 x 0,75	24 x 0,20	Red	B, M	Round	Ø5,8 ± 0,2 mm	H03VV-F	YES
418Axx12	2 x 0,75	24 x 0,20	Gold	B, M	Round	Ø5,8 ± 0,2 mm	H03VV-F	YES
418Axx13	2 x 0,75	24 x 0,20	Silver	B, M	Round	Ø5,8 ± 0,2 mm	H03VV-F	YES
418Axx78	2 x 0,75	24 x 0,20	White/Black	B, M	Round	Ø5,8 ± 0,2 mm	H03VV-F	YES
418Cxx07	3 x 0,75	24 x 0,20	White	B, M, G	Round	Ø6,2 ± 0,2 mm	H03VV-F	YES
418Cxx08	3 x 0,75	24 x 0,20	Black	B, M, G	Round	Ø6,2 ± 0,2 mm	H03VV-F	YES

Cores colors: B = blue, M = brown, G = yellow/green

xx = 25, 25m hard spool

xx = 00, 100m hard spool

TBI has the right to modify the articles without forewarning