

E1

3MP Super HD, Pan & Tilt & 2-Way Talk; Versatile Smart Home WiFi IP Camera

- 3MP Super HD
- Pan & Tilt
- Two-Way Audio

Specifications

Video & Audio	
Image Sensor	1/2.7" CMOS Sensors
Resolution	2304x1296 (3 Megapixels) @15fps
Lens	f=4.0mm fixed, F=2.0
Field of View	Horizontal: 84°; Vertical: 45°
Infrared Night Vision	Up to 12 meters (40ft); LED: 8pcs/14mil/850nm (Auto-switching with IR-cut filter)
Frame Rate	2-20fps (default: 15fps)
Code Rate	Main stream: 1024Kbps-4096Kbps (default: 2560Kbps); Sub stream: 128Kbps-512Kbps (default: 384Kbps)
Audio	Two-way audio
Power Requirements	
DC Power	DC 5.0V 2.1A
Interface	
Power Port	DC power port

Reset Button	YES
Ethernet Port	One 10M/100Mbps; RJ45
SD Card Slot	Supports Max. 512GB microSD card
Audio In/Out	Built-in microphone and speaker
Wi-Fi	
Wireless Standard	IEEE 802.11 b/g/n
Operating Frequency	2.4 GHz
Wireless Security	WPA/WPA2
Pan & Tilt	
PT Angle(Max.)	Pan: 355°; Tilt: 50°
Software	
Browsers Supported	Edge, Chrome, Firefox, Safari
OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
Protocols & Standards	SSL, TCP/IP, UDP, IPv4, UPnP, SMTP, NTP, DHCP, DNS, DDNS, P2P
User Access	Max. 20 users (1 admin & 19 users); Max. 12 simultaneous streams (2 main & 10 sub streams)
Other Features	
Smart Alarm	Person detection; Pet detection; Crying detection
Record Mode	Motion recording (default); Scheduled recording; 24/7 recording
Smart Home Compatibility	Google Assistant, Alexa
Working Environment	
Operating Temperature	-10°C~+55°C (14°F~131°F)
Operating Humidity	20% ~ 85%
Mechanical	
Dimension	Φ76x106mm

Weight	196g
Warranty	
Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/

Gallery & Specs



- 1. Daylight Sensor
- 2. IR LED
- 3. Lens
- 4. Status LED
- 5. Built-in Mic
- 6. Reset Button
- 7. microSD Card Slot



- 1. LAN Port
- 2. Speaker
- 3. Power