


EAN:	7021989032168
SG varenr.:	903216



Wattage:	7W
System effekt (W):	8W
Spænding:	220-240V
Maks. antal armaturer pr. afbryder:	B10: 19, B16: 30, C10: 31, C16: 51



Lyskilde:	LED
Lumen output:	550lm
Effekt:	69 lm/W
Farve temperatur:	2000-2800K
Farvegengivelse (Ra):	Ra>95
MacAdams faktor:	SDCM: 3
Levetid:	L90/B10>50.000
Driver, t/maks. udfald %:	100000/10
Lysfordeling:	Direkte
Optik:	Reflektor
Lysspredning:	42°
UGR:	UGR<19
Fotobiologisk sikkerhed:	RG 1



Type: Bagkantsdæmp

Isolationsklasse: Klasse II SELV
IP Klasse: IP54/IP20

Indeholder lyskilde med energiklasse:	F
Breeam:	Opfylder Hea 01 for flimmerfrit lys

Materiale:	Aluminium
Farve:	Hvid (RAL 9003)
Afskærmningsmateriale:	Hærdet glas

Montering: Indbygget, Indendørs / Udendørs
Tilslutning: 3 pol Linect / klemmerække

Højde (mm) H:	52
Diameter (mm) D:	90
Cut-out (mm):	83
Indbygningsdybde (mm):	51
Afstand til brandbart materiale i stråleretningen:	10mm
Vægt (kg) brutto/netto:	0.43 / 0.385

Forpakningsstørrelse (mm): 130 x 115 x 85

