

Floorstanding WC rimless combination with cistern without fixing holes for floor fixation

82765.1 000 N08 1



TECHNICAL DATA

Order no.	82765.1 000 N08 1
Certified to	EN 997
Specification	Washdown for 4,5/3-l-flush with cistern flushing mechanism, water condensation insulation, Dual-Flush (4,5/3-l-flush), water inlet bottom right 1/2" brass with white push button
Outlet	vertical
Weight	30,8 kg
Accessories incl.	Fresh WC-Sticks promotion kit (2 sticks)
Accessories excl.	Seat, order no. 89115.3 Seat and cover, order no. 89095.0, 89095.7, 89115.0, 89115.2 Seat and cover with automatic lowering system, order no. 89095.1, 89115.1 Fresh WC-Sticks (5 sticks), order no. 89165.3

Mounting acc. incl.	Mounting instruction, order no. 89965.4
Colours	see colour table

SPECIFICATION TEXT

Floorstanding WC rimless washdown Laufen-KOMPAS N, sanitary ceramic, with cistern Dual-Flush (4,5/3-l-flush), with white push button EN 997, 4,5/3-l-flush, dimensions 360 x 650 x 850 mm outlet vertical 70 mm

Special feature: rimless, concealed surfaces directing water are fully glazed throughout, vacuum checked

Further options / accessories: WC seat 89115.3, WC seat and cover, 89095.0, 89095.7, 89115.0, 89115.2, WC seat and cover with automatic lowering 89095.1, 89115.1, Fresh WC-Sticks (5 sticks) 89165.3

Order no. 82765.1 000 N08 1

TECHNICAL DRAWINGS / S 1 : 20

