



## Tee 90°, lige PE100 SDR17/17,6

- \* Segmentsvejst og forstærket
- \* Med påsvejste rør
- 5 bar gas / 10 bar vand
- \* Ingen trykreduktionsfaktor
- Spidsende, stuk/el svejsning

### Generelt:

- d20 - d225: PF 2 51 301 001d250 - d315: PF 2 51 301 002d355 - d800: PF 2 51 301 008

d [mm]	code	SP	weight [kg]
90	<b>753 200 813</b>	1	0,777
110	<b>753 200 814</b>	1	1,231
125	<b>753 200 815</b>	1	1,690
140	<b>753 200 816</b>	1	2,202
160	<b>753 200 817</b>	1	3,201
180	<b>753 200 818</b>	1	4,287
200	<b>753 200 819</b>	1	5,889
225	<b>753 200 820</b>	1	7,886
250	<b>753 200 821</b>	2	10,000
280	<b>753 200 802</b>	1	13,350
315	<b>753 200 803</b>	1	17,985
355	<b>753 200 804</b>	0	25,850
400	<b>753 200 805</b>	0	35,015
450	<b>753 200 806</b>	0	56,000
500	<b>753 200 807</b>	0	71,000
*	560 <b>753 200 808</b>	0	99,200
*	630 <b>753 200 809</b>	0	132,700
*	710 <b>753 201 920</b>	1	219,870
*	800 <b>753 201 921</b>	1	281,495

The technical data are not binding and not expressly warranted characteristics of the goods. They are subject to change. Our General Conditions of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.piping.georgfischer.com>