




Tee 90° lige PE100 SDR17,6

Generelt:

- Materiale: PE100
- Konventionel stuksvejsning iht. DS/INF 70-2
- IR = Infrarød-(IR Plus®) kompatibel. Svejseparameter: PE100



| d [mm] | FM | code | weight [kg] | L [mm] | L1 [mm] | e [mm] | PF |
|-----------|----|--------------------|----------------|-----------|------------|-----------|--------------|
| 50 | -- | 753 208 535 | 0,080 | 59 | 26 | 2,9 | 2 68 240 021 |
| 63 | -- | 753 208 536 | 0,187 | 71 | 25 | 3,6 | 2 68 240 021 |
| 75 | -- | 753 208 412 | 0,232 | 74 | 20 | 4,8 | 2 68 240 021 |
| 90 | -- | 753 208 413 | 0,408 | 90 | 20 | 5,6 | 2 68 240 021 |
| 110 | IR | 753 208 414 | 0,724 | 110 | 20 | 6,9 | 2 68 240 021 |
| 125 | IR | 753 208 540 | 1,175 | 124 | 27 | 7,1 | 2 68 240 029 |
| 140 | IR | 753 208 541 | 1,623 | 141 | 33 | 8,0 | 2 68 240 029 |
| 160 | IR | 753 208 542 | 2,431 | 160 | 40 | 9,1 | 2 68 240 029 |
| 180 | IR | 753 208 543 | 3,756 | 190 | 70 | 10,2 | 2 68 240 029 |
| 200 | IR | 753 208 544 | 5,243 | 210 | 70 | 11,4 | 2 68 240 029 |
| 225 | IR | 753 208 545 | 6,030 | 248 | 80 | 12,8 | 2 68 240 029 |
| 250 | -- | 753 208 546 | 9,964 | 272 | 90 | 14,2 | 2 68 240 029 |
| 280 | -- | 753 208 547 | 14,265 | 313 | 108 | 15,9 | 2 68 240 029 |
| 315 | -- | 753 208 548 | 22,284 | 348 | 114 | 17,9 | 2 68 240 029 |
| 355 | | 753 220 824 | 22,593 | 330 | 95 | 21,1 | 2 68 240 040 |
| 400 | | 753 220 825 | 30,500 | 345 | 104 | 23,7 | 2 68 240 040 |
| 450 | | 753 220 826 | 38,000 | 419 | 137 | 26,7 | 2 68 240 040 |
| 500 | | 753 220 827 | 52,600 | 460 | 159 | 29,7 | 2 68 240 040 |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland
 Phone +41 -(0)52-631 1111
 e-mail: info.ps@georgfischer.com
 Internet: <http://www.gfps.com>