



MULTI/JOINT® 3087 Plus Wide Range Spigot end, restraint, Uni/Fiksers

Model:

- Suitable for all kinds of pipe material
- Suitable for water and gas
- Ductile cast iron GGG45 body and clamping ring(s), acc. to EN-GJS-450-10
- RESICOAT® epoxy powder coating, according to GSK standards and EN 14901
- NBR or EPDM gasket, NBR acc. to EN 682 (-5°C up to +50°C), EPDM acc. to EN 681-1 (0°C up to +50°C)
- Angular deflection of max. 8° per socket at installation (based on the middle of the range)
- Stainless steel A4 quality (AISI 316) Uni/Fiksers
- Stainless steel A2 quality (AISI 304) or A4 quality (AISI 316) bolts, nuts and washers
- For restraint versions, on plastic pipes, the use of an insert stiffener (see accessories) is mandatory, check our technical information
- Hygiene protection included DN50 - DN600

DN (mm)	d3 (mm)	Range 1 (mm)	NBR / A4 Code	EPDM / A4 Code	Weight (kg)
50	63	46 - 71	709 335 010	709 335 310	3.400
100	110	104 - 132	709 335 016	709 335 316	7.400
150	160	154 - 192	709 335 020	709 335 320	11.600
200	200	192 - 232	709 335 029	709 335 329	21.100

DN (mm)	d3 (mm)	a (mm)	b (mm)	d (mm)	e (mm)	L (mm)	PN Water (bar)	PN Gas (bar)
50	63	204 - 219	164	100	3xM12	75	16	8
100	110	258 - 277	269	110	3xM16	120	16	8
150	160	289 - 317	304	120	4xM16	135	16	8
200	200	335 - 362	354	140	6xM16	145	16	8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>