




1 X 7 + 18 X 7

	Fune Ø mm.	Fili Est. Ø in mm.	Sezione metal. in mmq.	Carico di rottura Kg. F			Peso Kg./mt
				180 kg/mm ²	200 kg/mm ²	220 kg/mm ²	
	5	0,32	10,7	1.476	1.641	1.805	0,100
	6	0,40	16,7	2.126	2.362	2.599	0,140
	7	0,45	20,8	2.894	3.215	3.537	0,190
	8	0,50	24,7	3.780	4.200	4.620	0,230
	9	0,58	35,0	4.784	5.315	5.847	0,330
	10	0,65	41,7	5.906	6.562	7.218	0,390
	11	0,70	48,5	7.146	7.940	8.734	0,450
	12	0,80	63,2	8.504	9.449	10.394	0,580
	13	0,85	71,4	9.981	11.090	12.199	0,660
	14	0,90	80,0	11.575	12.862	14.148	0,740
	16	1,05	109,1	15.119	16.799	18.479	1,020
	18	1,15	142,9	19.135	21.261	23.387	1,310
	20	1,30	167,2	23.623	26.248	28.873	1,600
	22	1,45	208,0	28.584	31.760	34.936	1,920
	24	1,55	253,0	34.017	37.797	41.577	2,330
	26	1,70	301,0	39.923	44.359	48.795	2,660
	28	1,80	338,0	46.301	51.446	56.591	3,310
	30	1,93	338,8	53.152	59.058	64.964	3,680


1 X 7 + 34 X 7 W

	Fune Ø mm.	Fili Est. Ø in mm.	Sezione metal. in mmq.	Carico di rottura Kg. F			Peso Kg./mt
				200 kg/mm ²	220 kg/mm ²	240 kg/mm ²	
	8	0,40	30,25	4.790	5.269	5.748	0,273
	10	0,50	47,27	7.490	8.239	8.988	0,427
	11	0,55	57,20	9.060	9.966	10.872	0,520
	12	0,60	68,07	10.810	11.891	12.972	0,625
	13	0,65	79,89	12.640	13.904	15.168	0,730
	14	0,70	92,65	14.480	15.928	17.376	0,847
	15	0,75	106,36	16.820	18.502	20.184	0,966
	16	0,80	121,01	19.160	21.076	22.992	1,100
	17	0,85	136,61	21.610	23.771	25.932	1,230
	18	0,90	153,15	24.260	26.686	29.112	1,390
	19	0,95	170,64	27.010	29.711	32.412	1,540
	20	1,00	189,08	28.960	31.856	34.752	1,710
	22	1,10	228,79	36.280	39.908	43.536	2,070
	24	1,20	272,28	43.110	47.421	51.732	2,500
	25	1,25	295,44	46.780	51.458	56.136	2,651
	26	1,30	319,55	50.650	55.715	60.780	2,921
	28	1,40	370,60	58.700	64.570	70.440	3,390
	30	1,50	425,43	67.460	74.206	80.952	3,860
	32	1,60	484,04	76.740	84.414	92.088	4,401
	34	1,70	546,44	86.620	95.282	103.944	4,940
	36	1,80	612,62	97.120	106.832	116.544	5,531
	38	1,90	682,58	108.020	118.822	129.624	6,140

1 X 7+18 X 7 Compattato

	Fune Ø mm.	Fili Est. Ø in mm.	Sezione metal. in mmq.	Carico di rottura Kg. F	Peso Kg./mt
				220 kg/mmq	
	8	0,57	33,9	6.000	0,285
	9	0,64	42,8	7.600	0,370
	10	0,72	54,1	9.500	0,460
	11	0,78	63,5	11.300	0,557
	12	0,84	73,7	13.200	0,646
	12,5	0,87	79,0	14.100	0,692
	13	0,93	90,3	16.000	0,770
	14	0,99	102,3	18.500	0,870
15	1,08	121,8	21.650	1,060	
16	1,14	135,7	24.000	1,180	
17	1,23	158,0	27.900	1,370	
18	1,29	173,7	30.500	1,511	
20	1,44	216,5	38.000	1,878	
22	1,58	260,6	46.000	2,276	

1 X 7 + 34 X 7W Compattato

	Fune Ø mm.	Fili Est. Ø in mm.	Sezione metal. in mmq.	Carico di rottura Kg. F			Peso Kg./mt
				200 kg/mm ²	220 kg/mm ²	240 kg/mm ²	
	10	0,55	53,43	9.000	9.900	10.800	0,485
	11	0,59	64,65	10.691	11.760	12.829	0,575
	12	0,63	76,94	12.545	13.800	15.055	0,675
	12,5	0,66	83,48	13.182	14.500	15.818	0,735
	13	0,69	90,30	14.818	16.300	17.782	0,805
	14	0,75	104,72	17.273	19.000	20.727	0,950
	15	0,81	120,22	19.727	21.700	23.673	1,085
	16	0,87	136,78	22.727	25.000	27.273	1,250
	17	0,92	154,41	24.909	27.400	29.891	1,365
	18	0,97	173,11	28.727	31.600	34.473	1,560
	19	1,02	192,88	31.636	34.800	37.964	1,705
	20	1,08	213,72	34.909	38.400	41.891	1,910
	22	1,20	258,60	43.182	47.500	51.818	2,340
	24	1,29	307,76	49.909	54.900	59.891	2,700
	25	1,35	333,94	54.000	59.400	64.800	2,960
	26	1,41	361,19	58.727	64.600	70.473	3,213
	28	1,53	418,89	68.727	75.600	82.473	3,761
	30	1,62	480,87	78.273	86.100	93.927	4,160
	32	1,76	547,12	90.000	99.000	108.000	5,000

REMER PUO' PRODURRE TUTTI I CAVI QUI ILLUSTRATI NEL DIAMETRO RICHIESTO DAL CLIENTE