

AT + 6 X 36 WS




Fune Ø mm.	Fili Est. Ø in mm.	Sezione metal. in mmq.	Carico di rottura Kg. F			Peso Kg./mt
			180 kg/mm ²	200 kg/mm ²	220 kg/mm ²	
8	0,45	25,90	3.870	4.300	4.730	0,240
10	0,56	39,79	5.960	6.622	7.284	0,380
12	0,68	58,69	8.580	9.533	10.487	0,540
14	0,79	79,75	11.640	12.933	14.227	0,740
16	0,9	103,90	15.200	16.889	18.578	0,970
18	1,02	133,30	19.240	21.378	23.516	1,230
20	1,13	163,40	23.750	26.389	29.028	1,520
22	1,24	197,30	28.740	31.933	35.127	1,840
24	1,35	233,70	34.205	38.006	41.806	2,190
26	1,47	277,00	40.140	44.600	49.060	2,570
28	1,57	321,90	46.550	51.722	56.894	2,980
30	1,69	267,10	53.100	59.000	64.900	3,390
32	1,8	413,80	60.800	67.556	74.311	3,890

AT + 6 X 19 Seale



Fune Ø mm.	Fili Est. Ø in mm.	Sezione metal. in mmq.	Carico di rottura Kg. F			Peso Kg./mt
			180 kg/mm ²	200 kg/mm ²	220 kg/mm ²	
6	0,48	14,19	2.144	2.382	2.621	0,133
7	0,56	19,31	2.919	3.243	3.567	0,181
8	0,64	25,22	3.812	4.236	4.659	0,237
9	0,72	31,92	4.825	5.361	5.897	0,300
10	0,80	39,41	5.956	6.618	7.280	0,370
11	0,88	47,69	7.207	8.008	8.809	0,448
12	0,96	56,75	8.577	9.530	10.483	0,533
13	1,04	66,60	10.066	11.184	12.303	0,625
14	1,12	77,24	11.674	12.971	14.268	0,725
15	1,20	88,67	13.401	14.891	16.380	0,833
16	1,28	100,89	15.248	16.942	18.636	0,947
17	1,36	113,89	17.213	19.126	21.039	1,069
18	1,44	127,69	19.298	21.442	23.587	1,199
19	1,52	142,27	21.502	23.891	26.280	1,336
20	1,60	157,64	23.825	26.472	29.119	1,480
21	1,68	173,80	26.267	29.185	32.104	1,632
22	1,76	190,74	28.828	32.031	35.234	1,791

AM + 6 X 36 WS



Fune Ø mm.	Fili Est. Ø in mm.	Sezione metal. in mmq.	Carico di rottura Kg. F			Peso Kg./mt
			180 kg/mm ²	200 kg/mm ²	220 kg/mm ²	
8	0,45	30,10	4.180	4.644	5.109	0,264
10	0,56	46,40	6.410	7.122	7.834	0,420
12	0,68	68,30	9.230	10.256	11.281	0,600
14	0,79	92,70	12.560	13.956	15.351	0,820
16	0,9	120,80	16.420	18.244	20.069	1,070
18	1,02	154,90	20.780	23.089	25.398	1,350
20	1,13	190,00	25.650	28.500	31.350	1,670
22	1,24	229,30	31.030	34.478	37.926	2,030
24	1,35	272,10	36.950	41.056	45.161	2,410
26	1,47	322,00	43.350	48.167	52.983	2,830
28	1,57	373,90	50.250	55.833	61.417	3,280
30	1,69	427,10	57.790	64.211	70.632	3,760
32	1,8	475,80	65.650	72.944	80.239	4,280

AM + 6 X 19 Seale



Fune Ø mm.	Fili Est. Ø in mm.	Sezione metal. in mmq.	Carico di rottura Kg. F	Peso Kg./mt
			180 kg/mm ²	
10	0,80	46,13	7.000	0,410
12	0,96	66,43	10.150	0,590
14	1,12	90,41	13.900	0,810
16	1,28	118,09	18.300	1,060
18	1,44	149,46	23.000	1,330
20	1,60	184,52	28.400	1,640
22	1,76	223,27	34.400	1,990
24	1,92	265,71	40.700	2,350
26	2,04	311,84	47.900	2,770

REMER PUO' PRODURRE TUTTI I CAVI QUI ILLUSTRATI NEL DIAMETRO RICHIESTO DAL CLIENTE