

FC + 6 X 19 Seale



| Rope Ø. mm. | Ø. Out. Wire mm. | Steel cross section mm <sup>2</sup> | Min. Breaking Load kgf. |                        |                        | Weight Kg./mt |
|-------------|------------------|-------------------------------------|-------------------------|------------------------|------------------------|---------------|
|             |                  |                                     | 180 kg/mm <sup>2</sup>  | 200 kg/mm <sup>2</sup> | 220 kg/mm <sup>2</sup> |               |
| 6           | 0,48             | 14,19                               | 2.144                   | 2.382                  | 2.621                  | 0,133         |
| 7           | 0,56             | 19,31                               | 2.919                   | 3.243                  | 3.567                  | 0,181         |
| 8           | 0,64             | 25,22                               | 3.812                   | 4.236                  | 4.659                  | 0,237         |
| 9           | 0,72             | 31,92                               | 4.825                   | 5.361                  | 5.897                  | 0,300         |
| 10          | 0,80             | 39,41                               | 5.956                   | 6.618                  | 7.280                  | 0,370         |
| 11          | 0,88             | 47,69                               | 7.207                   | 8.008                  | 8.809                  | 0,448         |
| 12          | 0,96             | 56,75                               | 8.577                   | 9.530                  | 10.483                 | 0,533         |
| 13          | 1,04             | 66,60                               | 10.066                  | 11.184                 | 12.303                 | 0,625         |
| 14          | 1,12             | 77,24                               | 11.674                  | 12.971                 | 14.268                 | 0,725         |
| 15          | 1,20             | 88,67                               | 13.401                  | 14.891                 | 16.380                 | 0,833         |
| 16          | 1,28             | 100,89                              | 15.248                  | 16.942                 | 18.636                 | 0,947         |
| 17          | 1,36             | 113,89                              | 17.213                  | 19.126                 | 21.039                 | 1,069         |
| 18          | 1,44             | 127,69                              | 19.298                  | 21.442                 | 23.587                 | 1,199         |
| 19          | 1,52             | 142,27                              | 21.502                  | 23.891                 | 26.280                 | 1,336         |
| 20          | 1,60             | 157,64                              | 23.825                  | 26.472                 | 29.119                 | 1,480         |
| 21          | 1,68             | 173,80                              | 26.267                  | 29.185                 | 32.104                 | 1,632         |
| 22          | 1,76             | 190,74                              | 28.828                  | 32.031                 | 35.234                 | 1,791         |

FC + 6 X 25 Filler




| Rope Ø. mm. | Ø. Out. Wire mm. | Steel cross section mm <sup>2</sup> | Min. Breaking Load kgf. |                        |                        | Weight Kg./mt |
|-------------|------------------|-------------------------------------|-------------------------|------------------------|------------------------|---------------|
|             |                  |                                     | 180 kg/mm <sup>2</sup>  | 200 kg/mm <sup>2</sup> | 220 kg/mm <sup>2</sup> |               |
| 7           | 0,45             | 20,26                               | 2.979                   | 3.309                  | 3.640                  | 0,181         |
| 8           | 0,51             | 25,97                               | 3.890                   | 4.323                  | 4.755                  | 0,237         |
| 9           | 0,58             | 33,37                               | 4.924                   | 5.471                  | 6.018                  | 0,300         |
| 10          | 0,64             | 40,97                               | 6.079                   | 6.754                  | 7.429                  | 0,370         |
| 11          | 0,70             | 49,35                               | 7.355                   | 8.172                  | 8.990                  | 0,448         |
| 12          | 0,77             | 59,38                               | 8.753                   | 9.726                  | 10.698                 | 0,533         |
| 13          | 0,83             | 68,89                               | 10.273                  | 11.414                 | 12.556                 | 0,625         |
| 14          | 0,90             | 80,65                               | 11.914                  | 13.238                 | 14.562                 | 0,725         |
| 16          | 1,02             | 104,48                              | 15.561                  | 17.290                 | 19.019                 | 0,947         |
| 18          | 1,15             | 132,17                              | 19.695                  | 21.883                 | 24.071                 | 1,199         |
| 20          | 1,28             | 163,88                              | 24.314                  | 27.016                 | 29.718                 | 1,480         |
| 22          | 1,41             | 198,99                              | 29.420                  | 32.689                 | 35.958                 | 1,791         |

IWRC + 6 X 25 Filler



| Rope Ø. mm. | Ø. Out. Wire mm. | Steel cross section mm <sup>2</sup> | Min. Breaking Load kgf. |                        |                        | Weight Kg./mt |
|-------------|------------------|-------------------------------------|-------------------------|------------------------|------------------------|---------------|
|             |                  |                                     | 180 kg/mm <sup>2</sup>  | 200 kg/mm <sup>2</sup> | 220 kg/mm <sup>2</sup> |               |
| 7           | 0,45             | 23,46                               | 3.217                   | 3.574                  | 3.931                  | 0,202         |
| 8           | 0,51             | 30,14                               | 4.201                   | 4.668                  | 5.135                  | 0,264         |
| 9           | 0,58             | 38,65                               | 5.317                   | 5.908                  | 6.499                  | 0,334         |
| 10          | 0,64             | 47,49                               | 6.565                   | 7.294                  | 8.023                  | 0,413         |
| 11          | 0,70             | 57,24                               | 7.943                   | 8.826                  | 9.708                  | 0,499         |
| 12          | 0,77             | 68,77                               | 9.453                   | 10.503                 | 11.554                 | 0,594         |
| 13          | 0,83             | 79,91                               | 11.094                  | 12.327                 | 13.560                 | 0,697         |
| 14          | 0,90             | 93,44                               | 12.867                  | 14.296                 | 15.726                 | 0,809         |
| 16          | 1,02             | 121,18                              | 16.805                  | 18.673                 | 20.540                 | 1,056         |
| 18          | 1,15             | 153,50                              | 21.269                  | 23.633                 | 25.996                 | 1,337         |
| 20          | 1,28             | 189,97                              | 26.258                  | 29.176                 | 32.094                 | 1,650         |
| 22          | 1,41             | 230,56                              | 31.773                  | 35.303                 | 38.833                 | 1,997         |

IWRC + 6 X 25 Filler Compacted



| Rope Ø. mm. | Ø. Out. Wire mm. | Steel cross section mm <sup>2</sup> | Min. Breaking Load kgf. |                        |                        | Weight Kg./mt |
|-------------|------------------|-------------------------------------|-------------------------|------------------------|------------------------|---------------|
|             |                  |                                     | 180 kg/mm <sup>2</sup>  | 200 kg/mm <sup>2</sup> | 220 kg/mm <sup>2</sup> |               |
| 7           | 0,48             | 25,81                               | 3.538                   | 3.931                  | 4.325                  | 0,222         |
| 8           | 0,54             | 33,15                               | 4.621                   | 5.135                  | 5.648                  | 0,290         |
| 9           | 0,62             | 42,52                               | 5.849                   | 6.499                  | 7.149                  | 0,368         |
| 10          | 0,68             | 52,24                               | 7.221                   | 8.023                  | 8.826                  | 0,454         |
| 11          | 0,75             | 62,96                               | 8.737                   | 9.708                  | 10.679                 | 0,549         |
| 12          | 0,82             | 75,65                               | 10.398                  | 11.554                 | 12.709                 | 0,653         |
| 13          | 0,88             | 87,90                               | 12.204                  | 13.560                 | 14.916                 | 0,767         |
| 14          | 0,96             | 102,78                              | 14.153                  | 15.726                 | 17.298                 | 0,889         |
| 16          | 1,09             | 133,30                              | 18.486                  | 20.540                 | 22.594                 | 1,162         |
| 18          | 1,22             | 168,85                              | 23.396                  | 25.996                 | 28.595                 | 1,470         |
| 20          | 1,36             | 208,97                              | 28.884                  | 32.094                 | 35.303                 | 1,815         |
| 22          | 1,50             | 253,62                              | 34.950                  | 38.833                 | 42.717                 | 2,250         |
| 24          | 1,64             | 301,58                              | 41.593                  | 46.215                 | 50.836                 | 2,614         |
| 26          | 1,77             | 352,43                              | 48.814                  | 54.238                 | 59.662                 | 3,067         |
| 28          | 1,91             | 408,58                              | 56.613                  | 62.903                 | 69.194                 | 3,557         |
| 30          | 2,04             | 470,16                              | 64.990                  | 72.211                 | 79.432                 | 4,084         |
| 32          | 2,18             | 536,06                              | 73.944                  | 82.160                 | 90.376                 | 4,646         |
| 34          | 2,32             | 604,85                              | 83.475                  | 92.751                 | 102.026                | 5,245         |
| 36          | 2,45             | 676,05                              | 93.585                  | 103.983                | 114.382                | 5,881         |

FOLLOWING CLIENT'S NEEDS, REMER IS ABLE TO PRODUCE THE OVER - DISPLAYED WIRE ROPES IN ALL REQUESTED DIAMETERS.

