

AT + 6 X 19 Seale



| Fune<br>Ø<br>mm. | Fili Est.<br>Ø<br>in mm. | Sezione<br>metal. in<br>mmq. | Carico di<br>rottura Kg. F |                           |                           | Peso<br>Kg./mt |
|------------------|--------------------------|------------------------------|----------------------------|---------------------------|---------------------------|----------------|
|                  |                          |                              | 180<br>kg/mm <sup>2</sup>  | 200<br>kg/mm <sup>2</sup> | 220<br>kg/mm <sup>2</sup> |                |
| 6                | 0,48                     | 14,19                        | 2.144                      | 2.382                     | 2.621                     | 0,133          |
| 7                | 0,56                     | 19,31                        | 2.919                      | 3.243                     | 3.567                     | 0,181          |
| 8                | 0,64                     | 25,22                        | 3.812                      | 4.236                     | 4.659                     | 0,237          |
| 9                | 0,72                     | 31,92                        | 4.825                      | 5.361                     | 5.897                     | 0,300          |
| 10               | 0,80                     | 39,41                        | 5.956                      | 6.618                     | 7.280                     | 0,370          |
| 11               | 0,88                     | 47,69                        | 7.207                      | 8.008                     | 8.809                     | 0,448          |
| 12               | 0,96                     | 56,75                        | 8.577                      | 9.530                     | 10.483                    | 0,533          |
| 13               | 1,04                     | 66,60                        | 10.066                     | 11.184                    | 12.303                    | 0,625          |
| 14               | 1,12                     | 77,24                        | 11.674                     | 12.971                    | 14.268                    | 0,725          |
| 15               | 1,20                     | 88,67                        | 13.401                     | 14.891                    | 16.380                    | 0,833          |
| 16               | 1,28                     | 100,89                       | 15.248                     | 16.942                    | 18.636                    | 0,947          |
| 17               | 1,36                     | 113,89                       | 17.213                     | 19.126                    | 21.039                    | 1,069          |
| 18               | 1,44                     | 127,69                       | 19.298                     | 21.442                    | 23.587                    | 1,199          |
| 19               | 1,52                     | 142,27                       | 21.502                     | 23.891                    | 26.280                    | 1,336          |
| 20               | 1,60                     | 157,64                       | 23.825                     | 26.472                    | 29.119                    | 1,480          |
| 21               | 1,68                     | 173,80                       | 26.267                     | 29.185                    | 32.104                    | 1,632          |
| 22               | 1,76                     | 190,74                       | 28.828                     | 32.031                    | 35.234                    | 1,791          |

AM + 6 X 25 Filler



| Fune<br>Ø<br>mm. | Fili Est.<br>Ø<br>in mm. | Sezione<br>metal. in<br>mmq. | Carico di<br>rottura Kg. F |                           |                           | Peso<br>Kg./mt |
|------------------|--------------------------|------------------------------|----------------------------|---------------------------|---------------------------|----------------|
|                  |                          |                              | 180<br>kg/mm <sup>2</sup>  | 200<br>kg/mm <sup>2</sup> | 220<br>kg/mm <sup>2</sup> |                |
| 7                | 0,45                     | 23,46                        | 3.217                      | 3.574                     | 3.931                     | 0,202          |
| 8                | 0,51                     | 30,14                        | 4.201                      | 4.668                     | 5.135                     | 0,264          |
| 9                | 0,58                     | 38,65                        | 5.317                      | 5.908                     | 6.499                     | 0,334          |
| 10               | 0,64                     | 47,49                        | 6.565                      | 7.294                     | 8.023                     | 0,413          |
| 11               | 0,70                     | 57,24                        | 7.943                      | 8.826                     | 9.708                     | 0,499          |
| 12               | 0,77                     | 68,77                        | 9.453                      | 10.503                    | 11.554                    | 0,594          |
| 13               | 0,83                     | 79,91                        | 11.094                     | 12.327                    | 13.560                    | 0,697          |
| 14               | 0,90                     | 93,44                        | 12.867                     | 14.296                    | 15.726                    | 0,809          |
| 16               | 1,02                     | 121,18                       | 16.805                     | 18.673                    | 20.540                    | 1,056          |
| 18               | 1,15                     | 153,50                       | 21.269                     | 23.633                    | 25.996                    | 1,337          |
| 20               | 1,28                     | 189,97                       | 26.258                     | 29.176                    | 32.094                    | 1,650          |
| 22               | 1,41                     | 230,56                       | 31.773                     | 35.303                    | 38.833                    | 1,997          |

AT + 6 X 25 Filler



| Fune<br>Ø<br>mm. | Fili Est.<br>Ø<br>in mm. | Sezione<br>metal. in<br>mmq. | Carico di<br>rottura Kg. F |                           |                           | Peso<br>Kg./mt |
|------------------|--------------------------|------------------------------|----------------------------|---------------------------|---------------------------|----------------|
|                  |                          |                              | 180<br>kg/mm <sup>2</sup>  | 200<br>kg/mm <sup>2</sup> | 220<br>kg/mm <sup>2</sup> |                |
| 7                | 0,45                     | 20,26                        | 2.979                      | 3.309                     | 3.640                     | 0,181          |
| 8                | 0,51                     | 25,97                        | 3.890                      | 4.323                     | 4.755                     | 0,237          |
| 9                | 0,58                     | 33,37                        | 4.924                      | 5.471                     | 6.018                     | 0,300          |
| 10               | 0,64                     | 40,97                        | 6.079                      | 6.754                     | 7.429                     | 0,370          |
| 11               | 0,70                     | 49,35                        | 7.355                      | 8.172                     | 8.990                     | 0,448          |
| 12               | 0,77                     | 59,38                        | 8.753                      | 9.726                     | 10.698                    | 0,533          |
| 13               | 0,83                     | 68,89                        | 10.273                     | 11.414                    | 12.556                    | 0,625          |
| 14               | 0,90                     | 80,65                        | 11.914                     | 13.238                    | 14.562                    | 0,725          |
| 16               | 1,02                     | 104,48                       | 15.561                     | 17.290                    | 19.019                    | 0,947          |
| 18               | 1,15                     | 132,17                       | 19.695                     | 21.883                    | 24.071                    | 1,199          |
| 20               | 1,28                     | 163,88                       | 24.314                     | 27.016                    | 29.718                    | 1,480          |
| 22               | 1,41                     | 198,99                       | 29.420                     | 32.689                    | 35.958                    | 1,791          |

AM 6 X 25 Filler Compattato



| Fune<br>Ø<br>mm. | Fili Est.<br>Ø<br>in mm. | Sezione<br>metal. in<br>mmq. | Carico di<br>rottura Kg. F |                           |                           | Peso<br>Kg./mt |
|------------------|--------------------------|------------------------------|----------------------------|---------------------------|---------------------------|----------------|
|                  |                          |                              | 180<br>kg/mm <sup>2</sup>  | 200<br>kg/mm <sup>2</sup> | 220<br>kg/mm <sup>2</sup> |                |
| 7                | 0,48                     | 25,81                        | 3.538                      | 3.931                     | 4.325                     | 0,222          |
| 8                | 0,54                     | 33,15                        | 4.621                      | 5.135                     | 5.648                     | 0,290          |
| 9                | 0,62                     | 42,52                        | 5.849                      | 6.499                     | 7.149                     | 0,368          |
| 10               | 0,68                     | 52,24                        | 7.221                      | 8.023                     | 8.826                     | 0,454          |
| 11               | 0,75                     | 62,96                        | 8.737                      | 9.708                     | 10.679                    | 0,549          |
| 12               | 0,82                     | 75,65                        | 10.398                     | 11.554                    | 12.709                    | 0,653          |
| 13               | 0,88                     | 87,90                        | 12.204                     | 13.560                    | 14.916                    | 0,767          |
| 14               | 0,96                     | 102,78                       | 14.153                     | 15.726                    | 17.298                    | 0,889          |
| 16               | 1,09                     | 133,30                       | 18.486                     | 20.540                    | 22.594                    | 1,162          |
| 18               | 1,22                     | 168,85                       | 23.396                     | 25.996                    | 28.595                    | 1,470          |
| 20               | 1,36                     | 208,97                       | 28.884                     | 32.094                    | 35.303                    | 1,815          |
| 22               | 1,50                     | 253,62                       | 34.950                     | 38.833                    | 42.717                    | 2,250          |
| 24               | 1,64                     | 301,58                       | 41.593                     | 46.215                    | 50.836                    | 2,614          |
| 26               | 1,77                     | 352,43                       | 48.814                     | 54.238                    | 59.662                    | 3,067          |
| 28               | 1,91                     | 408,58                       | 56.613                     | 62.903                    | 69.194                    | 3,557          |
| 30               | 2,04                     | 470,16                       | 64.990                     | 72.211                    | 79.432                    | 4,084          |
| 32               | 2,18                     | 536,06                       | 73.944                     | 82.160                    | 90.376                    | 4,646          |
| 34               | 2,32                     | 604,85                       | 83.475                     | 92.751                    | 102.026                   | 5,245          |
| 36               | 2,45                     | 676,05                       | 93.585                     | 103.983                   | 114.382                   | 5,881          |

REMER PUO' PRODURRE TUTTI I CAVI QUI ILLUSTRATI NEL DIAMETRO RICHIESTO DAL CLIENTE