


AM + 8 X 36WS




Fune Ø mm.	Fili Est. Ø in mm.	Sezione metal. in mmq.	Carico di rottura Kg. F			Peso Kg./mt
			180 kg/mm ²	200 kg/mm ²	220 kg/mm ²	
10	0,46	47,03	6.235	6.928	7.621	0,435
11	0,51	56,90	7.545	8.383	9.221	0,526
12	0,56	67,72	8.979	9.976	10.974	0,626
13	0,60	79,48	10.537	11.708	12.879	0,735
14	0,65	92,17	12.221	13.579	14.937	0,852
16	0,74	120,39	15.962	17.736	19.509	1,113
18	0,83	152,37	20.202	22.447	24.691	1,409
20	0,93	188,11	24.941	27.712	30.483	1,740
22	1,02	227,61	30.178	33.532	36.885	2,105
24	1,11	270,88	35.915	39.905	43.896	2,505
26	1,20	317,90	42.150	46.833	51.517	2,940
28	1,30	368,69	48.884	54.316	59.747	3,410
30	1,39	423,24	56.117	62.352	68.587	3,914
32	1,48	481,56	63.848	70.943	78.037	4,453
34	1,57	543,63	72.079	80.088	88.096	5,027
36	1,67	609,47	80.808	89.787	98.766	5,636
38	1,76	679,07	90.036	100.040	110.044	6,280
40	1,85	752,43	99.763	110.848	121.933	6,958
42	1,94	829,55	109.989	122.210	134.431	7,672
44	2,04	910,44	120.713	134.126	147.539	8,420
46	2,13	995,09	131.937	146.596	161.256	9,202
48	2,22	1.083,50	143.659	159.621	175.583	10,020

AM + 4 X 7 + 4 X 7 + 4 X 7 + 8 X 25




Fune Ø mm.	Fili Est. Ø in mm.	Sezione metal. in mmq.	Carico di rottura Kg. F			Peso Kg./mt
			180 kg/mm ²	200 kg/mm ²	220 kg/mm ²	
12	0,63	76	11.820	13.150	14.465	0,650
14	0,73	105	16.210	18.080	19.888	0,880
16	0,84	135	21.210	23.550	25.905	1,159
18	0,94	172	26.610	29.770	32.747	1,458
20	1,05	215	33.340	37.010	40.711	1,821
22	1,15	258	39.870	44.350	48.785	2,183
24	1,25	306	47.310	52.610	57.871	2,587
26	1,36	357	55.260	61.380	67.518	3,019
28	1,46	416	64.340	71.480	78.628	3,519
30	1,57	481	74.430	82.690	90.959	4,071
32	1,67	546	84.530	93.910	103.301	4,621
34	1,78	617	95.440	106.070	116.677	5,220
36	1,88	684	105.940	117.675	129.443	5,790
38	1,99	768	119.000	132.155	145.371	6,501
40	2,09	846	130.930	145.514	160.065	7,157
42	2,20	930	143.980	159.890	175.879	7,867
44	2,30	1020	157.850	175.390	192.929	8,629
46	2,40	1115	172.625	191.910	211.101	9,438

1 X 25 + 8 X 7 + 8 X 25



Fune Ø mm.	Fili Est. Ø in mm.	Sezione metal. in mmq.	Carico di rottura Kg. F			Peso Kg./mt
			180 kg/mm ²	200 kg/mm ²	220 kg/mm ²	
8	0,42	37,4	5.472	6.080	6.688	0,285
8,5	0,44	42,3	6.177	6.864	7.550	0,316
10	0,52	58,5	8.550	9.500	10.450	0,434
11	0,58	70,8	10.346	11.495	12.645	0,522
12	0,63	84,2	12.312	13.680	15.048	0,643
14	0,73	114,6	16.758	18.620	20.482	0,853
16	0,84	149,7	21.888	24.320	26.752	1,160
18	0,94	189,5	27.702	30.780	33.858	1,450
20	1,05	234,0	34.200	38.000	41.800	1,750
22	1,15	283,1	41.382	45.980	50.578	2,180
24	1,25	336,9	49.248	54.720	60.192	2,570
26	1,36	395,4	57.798	64.220	70.642	3,020
28	1,46	458,6	67.032	74.480	81.928	3,530


AM + 4 X 7 + 4 X 7 + 4 X 7 + 8 X 25 Compattato



Fune Ø mm.	Fili Est. Ø in mm.	Sezione metal. in mmq.	Carico di rottura Kg. F			Peso Kg./mt
			180 kg/mm ²	200 kg/mm ²	220 kg/mm ²	
12	0,68	81	12.330	13.660	15.026	0,679
14	0,79	109	16.620	18.660	20.526	0,918
16	0,90	144	22.020	24.470	26.917	1,214
18	1,01	184	28.140	31.200	34.320	1,545
20	1,13	225	34.360	38.230	42.053	1,892
22	1,24	274	41.910	46.600	51.260	2,305
24	1,35	323	49.350	54.040	59.444	2,714
26	1,47	379	57.910	64.340	70.774	3,186
28	1,58	436	66.680	74.130	81.543	3,669
30	1,69	504	77.090	85.750	94.325	4,240
32	1,80	578	88.510	98.300	108.130	4,862
34	1,92	644	98.500	109.410	120.351	5,413
36	2,03	724	110.740	123.180	135.498	6,090
38	2,14	809	123.790	137.150	150.865	6,803
40	2,25	892	136.540	151.730	166.903	7,503
42	2,37	983	150.300	167.020	183.722	8,263
44	2,48	1.078	164.990	183.240	201.564	9,067


REMER PUO' PRODURRE TUTTI I CAVI QUI ILLUSTRATI NEL DIAMETRO RICHIESTO DAL CLIENTE.

AM + 6 X 36 WS Compattato



Fune Ø mm.	Fili Est. Ø in mm.	Sezione metal. in mmq.	Carico di rottura Kg. F			Peso Kg./mt
			180 kg/mm ²	200 kg/mm ²	220 kg/mm ²	
16	0,94	130,30	18.533	20.592	22.651	1,103
18	1,06	165,50	23.530	26.144	28.758	1,401
20	1,16	200,30	28.480	31.644	34.808	1,695
22	1,23	244,00	34.703	38.559	42.415	2,066
24	1,40	289,70	41.192	45.769	50.346	2,453
26	1,53	342,50	48.709	54.121	59.533	2,901
28	1,65	398,10	56.607	62.897	69.187	3,371
32	1,86	515,30	73.282	81.424	89.566	4,364
36	2,10	649,70	92.387	102.653	112.918	5,502
40	2,32	799,00	113.740	126.378	139.016	6,773
44	2,56	968,20	137.681	152.979	168.277	8,199

AM + 8 X 36WS




Fune Ø mm.	Fili Est. Ø in mm.	Sezione metal. in mmq.	Carico di rottura Kg. F			Peso Kg./mt
			180 kg/mm ²	200 kg/mm ²	220 kg/mm ²	
10	0,46	47,03	6.235	6.928	7.621	0,435
11	0,51	56,90	7.545	8.383	9.221	0,526
12	0,56	67,72	8.979	9.976	10.974	0,626
13	0,60	79,48	10.537	11.708	12.879	0,735
14	0,65	92,17	12.221	13.579	14.937	0,852
16	0,74	120,39	15.962	17.736	19.509	1,113
18	0,83	152,37	20.202	22.447	24.691	1,409
20	0,93	188,11	24.941	27.712	30.483	1,740
22	1,02	227,61	30.178	33.532	36.885	2,105
24	1,11	270,88	35.915	39.905	43.896	2,505
26	1,20	317,90	42.150	46.833	51.517	2,940
28	1,30	368,69	48.884	54.316	59.747	3,410
30	1,39	423,24	56.117	62.352	68.587	3,914
32	1,48	481,56	63.848	70.943	78.037	4,453
34	1,57	543,63	72.079	80.088	88.096	5,027
36	1,67	609,47	80.808	89.787	98.766	5,636
38	1,76	679,07	90.036	100.040	110.044	6,280
40	1,85	752,43	99.763	110.848	121.933	6,958
42	1,94	829,55	109.989	122.210	134.431	7,672
44	2,04	910,44	120.713	134.126	147.539	8,420
46	2,13	995,09	131.937	146.596	161.256	9,202
48	2,22	1.083,50	143.659	159.621	175.583	10,020

1 X 7+18 X 7 Compattato



Fune Ø mm.	Fili Est. Ø in mm.	Sezione metal. in mmq.	Carico di rottura Kg. F	Peso Kg./mt
			220 kg/mm ²	
8	0,57	33,9	6.000	0,285
9	0,64	42,8	7.600	0,370
10	0,72	54,1	9.500	0,460
11	0,78	63,5	11.300	0,557
12	0,84	73,7	13.200	0,646
12,5	0,87	79,0	14.100	0,692
13	0,93	90,3	16.000	0,770
14	0,99	102,3	18.500	0,870
15	1,08	121,8	21.650	1,060
16	1,14	135,7	24.000	1,180
17	1,23	158,0	27.900	1,370
18	1,29	173,7	30.500	1,511
20	1,44	216,5	38.000	1,878
22	1,58	260,6	46.000	2,276

1 X 7 + 34 X 7W Compattato



Fune Ø mm.	Fili Est. Ø in mm.	Sezione metal. in mmq.	Carico di rottura Kg. F			Peso Kg./mt
			200 kg/mm ²	220 kg/mm ²	240 kg/mm ²	
10	0,55	53,43	9.000	9.900	10.800	0,485
11	0,59	64,65	10.691	11.760	12.829	0,575
12	0,63	76,94	12.545	13.800	15.055	0,675
12,5	0,66	83,48	13.182	14.500	15.818	0,735
13	0,69	90,30	14.818	16.300	17.782	0,805
14	0,75	104,72	17.273	19.000	20.727	0,950
15	0,81	120,22	19.727	21.700	23.673	1,085
16	0,87	136,78	22.727	25.000	27.273	1,250
17	0,92	154,41	24.909	27.400	29.891	1,365
18	0,97	173,11	28.727	31.600	34.473	1,560
19	1,02	192,88	31.636	34.800	37.964	1,705
20	1,08	213,72	34.909	38.400	41.891	1,910
22	1,20	258,60	43.182	47.500	51.818	2,340
24	1,29	307,76	49.909	54.900	59.891	2,700
25	1,35	333,94	54.000	59.400	64.800	2,960
26	1,41	361,19	58.727	64.600	70.473	3,213
28	1,53	418,89	68.727	75.600	82.473	3,761
30	1,62	480,87	78.273	86.100	93.927	4,160
32	1,76	547,12	90.000	99.000	108.000	5,000

REMER PUO' PRODURRE TUTTI I CAVI QUI ILLUSTRATI NEL DIAMETRO RICHIESTO DAL CLIENTE.