

## 床垫用钢丝 Bedding & Seating

### Spring Wire

用于家具、汽车座靠垫、室内装饰等冷拉圆形截面碳素弹簧钢丝。

采用标准及技术要求

BS5216 机械用铅淬火冷拉弹簧钢丝

ISO/CD8458-2 铅淬火冷拉碳素丝碳素弹簧钢丝

GB/T4357



公称直径 Nominal dia. mm	抗拉强度 tensile strength MPa		扭转 torsion 次数	直径允 许偏差 tolerance mm	圈径 Cast dia. mm	螺旋排绕 (开口距) Helix mm	包装 (件重 kg) packing	
							纸筒 Cardboard core	线架 Stem
1.30	1660-1860	1700-1900	22	±0.02	533-635	0-102		500.0
1.40	1660-1860	1750-1900	22	±0.02	533-635	0-102		500.0
1.60	1620-1820	1800-2030	22	±0.02	635-737	0-102		800.0
1.70	1540-1720	1700-1900	22	±0.02	635-737	0-102		800.0
1.75	1540-1720	1700-1900	22	±0.02	635-737	0-102		800.0
1.80	1590-1790	1800-2030	22	±0.02	635-737	0-102		800.0
1.93	1570-1750	1620-1820	22	±0.02	635-737	0-102		800.0
2.00	1600-1800	1790-2000	22	±0.02	635-737	0-102		800.0
2.10	1600-1800	1790-2000	22	±0.02	635-737	0-102		800.0
2.18	1550-1750	1650-1800	22	±0.02	635-737	0-102		1000.0
2.24	1580-1680	1650-1800	22	±0.02	635-737	0-102		1000.0
2.30	1650-1800	1850-2030	20	±0.02	635-737	0-102		1000.0
2.32	1550-1750	1600-1800	20	±0.02	635-737	0-102		1000.0
2.41	1660-1790	1700-1850	18	±0.02	635-737	0-102		1000.0
2.50	1480-1680	1700-1850	18	±0.02	635-737	0-102		1000.0
3.00	1400-1600	1800-1950	15	±0.02	737-837	0-102		1000.0
3.55	1400-1600	1550-1700	15	±0.03	737-837	0-102		1000.0
3.88	1400-1600	1550-1700	15	±0.03	737-837	0-102		1000.0
4.88	1350-1550	1480-1600	15	±0.03	737-837	0-102		1000.0
5.00	1350-1550	1480-1600	15	±0.03	737-837	0-102		1000.0
6.00	620-830	1250-1450	10	±0.03	737-837	0-102		1000.0