

RIV606

Automatic feeder for blind rivets
to be combined with a tool for blind rivets

RIV616

Automatic feeder for rivet nuts
to be combined with a tool for rivet nuts



Code 4879100 (Ø 2.4-3.0-3.2)

Code 4639000 (Ø 3.4-4.8)

Code 4850900 (Ø 6.0-6.4)

For blind rivets from Ø 2.4 to 6.4 (the length of the nail must be less than 50 mm).

For Ø 3.4-4.8 the head must not exceed 10 mm.

The new Rivit automatic blind rivet feeder is a pneumatic and electric tool, which allows to insert the blind rivet directly inside the head of the tool, reducing the riveting implementation time.

This solution avoids the contact between the hand of operator and the riveting tool, ensuring complete safety.

It can be used only with riveting tools fitted with vacuum exhaust and mandrel storage systems, such as RIV502 / RIV503 / RIV504 / RIV505.

Technical data and features

Voltage	220 V - 50 Hz
Air pressure	2/4 bar
Installed power	100 W
Dimensions (width x depth x height)	340x530/630x340 mm
Weight	34 kg



Code 4835200

For rivet nuts from M3 to M8, hexagonal or cylindrical shank, dome, countersunk, reduced head.

The new Rivit automatic rivet nuts feeder is a pneumatic and electric tool, which allows to insert the rivet nuts directly on the head of the tool, reducing the riveting implementation time.

It can be used with many riveting tools for rivet nuts such as RIV938 / RIV939 / RIV941.

Choose the correct kit according to the size of the rivet nut to be placed, and add it to the order (see kits table).

Kits for RIV616

Rivet nut measure	Kit	Kit code
M3	616/03	5004800
M4	616/04	5004900
M5	616/05	5005000
M6	616/06	5005100
M8	616/08	5005200

Technical data and features

Voltage	220 V - 50 Hz
Air pressure	2/4 bar
Dimensions (width x depth x height)	340x530x340 mm
Weight	32 kg

