

**Features:**

- Isolated mounting base 3000V~
- Pressure contact technology with Increased power cycling capability
- Space and weight saving
- Typical Applications**
- AC/DC Motor drives
- Various rectifiers
- DC supply for PWM inverter

V _{RRM} , V _{DRM}	Type & Outline		
	MTx	MFx	
800V	MTx300-08-413F3D	MFx300-08-413F3D	
1000V	MTx300-10-413F3D	MFx300-10-413F3D	
1200V	MTx300-12-413F3D	MFx300-12-413F3D	
1400V	MTx300-14-413F3D	MFx300-14-413F3D	
1600V	MTx300-16-413F3D	MFx300-16-413F3D	
1800V	MTx300-18-413F3D	MFx300-18-413F3D	
1800V	MT300-18-413F3DG		

MTx stands for any type of **MTC**, **MTA**, **MTK**MFx stands for any type of **MFC**, **MFA**, **MFK**

SYMBOL	CHARACTERISTIC	TEST CONDITIONS	T _J (°C)	VALUE			UNIT
				Min	Type	Max	
I _{T(AV)}	Mean on-state current	180° half sine wave 50Hz Single side cooled, T _C =85°C	125			300	A
I _{T(RMS)}	RMS on-state current					471	A
I _{DRM} I _{RRM}	Repetitive peak current	at V _{DRM} at V _{RRM}	125			35	mA
I _{TSM}	Surge on-state current	V _R =60%V _{RRM} , t=10ms half sine,	125			9.1	kA
I ² t	I ² t for fusing coordination					414	10 ³ A ² s
V _{TO}	Threshold voltage	I _{TM} =900A	125			0.85	V
r _T	On-state slope resistance					0.72	mΩ
V _{TM}	Peak on-state voltage	I _{TM} =900A	25			1.56	V
dV/dt	Critical rate of rise of off-state voltage	V _{DM} =67%V _{DRM}	125			1000	V/μs
dI/dt	Critical rate of rise of on-state current	Gate source 1.5A t _r ≤0.5μs Repetitive	125			200	A/μs
I _{GT}	Gate trigger current	V _A =12V, I _A =1A	25	30		180	mA
V _{GT}	Gate trigger voltage			0.7		2.5	V
I _H	Holding current			10		180	mA
I _L	Latching current					1000	mA
V _{GD}	Non-trigger gate voltage	V _{DM} =67%V _{DRM}	125			0.20	V
R _{th(j-c)}	Thermal resistance Junction to case	Single side cooled per chip				0.10	°C/W
R _{th(c-h)}	Thermal resistance case to heatsink	Single side cooled per chip				0.04	°C/W
V _{iso}	Isolation voltage	50Hz, R.M.S, t=1min, I _{iso} :1mA(MAX)		3000			V
F _m	Terminal connection torque(M8)			10.0		12.0	N·m
	Mounting torque(M6)			4.5		6.0	N·m
T _{vj}	Junction temperature			-40		125	°C
T _{stg}	Stored temperature			-40		125	°C
W _t	Weight				770		g
Outline		413F3D					




Fig.1




Fig.2




Fig.3




Fig.4




Fig.5




Fig.6




Fig.7




Fig.8





Fig.9

Outline:**Unmarked dimensional tolerance: ±0.5mm**

TECHSEM reserves the right to change specifications without notice.




Fig.10

