



Key Parameters

V_{RRM}	= 1600V
$I_{F(AV)}$	= 320A
I_{FSM}	= 6000A
$V_{F(TO)}$	= 0.85V
r_F	= 0.60mΩ

Features

- Full blocking capability over wide temperature range
- Hermetic metal case with glass insulator
- Threaded Stud

Applications

- Power Supplies
- Uncontrolled Rectifiers
- Battery Chargers

Ordering Information


MS D	240	N	XX	M	B
Rectifier Diode	Current code	Polarity R= Stud Anode N= Stud Cathode	Voltage Code Code X 100 = V_{RRM}	Stud Threads M = Stud M16 X 1.5 U = 3/4" -16UNF-2A M1 = Stud M20 X 1.5	Technology B = Solder Bond Technology
Order Code MS D240N16MB : 1600V V_{RRM} , M16 Stud, Diode with stud Cathode					

Prepared by : ABA	Date of Publication : 25.03.2015
Approved by : RBS	Revision : 0

Symbol	Characteristic	Conditions	T _j [°C]	Value	Unit
BLOCKING					
V _{RRM}	Repetitive peak reverse voltage		180	200 - 1600	V
V _{RSM}	Non-repetitive peak reverse voltage		180	300 - 1700	V
I _{RRM}	Repetitive peak reverse current	V = V _{RRM}	180	30	mA
CONDUCTING					
I _{F(AV)}	Mean forward current	180° sin ,50 Hz, T _c =100°C T _c =125°C		320 240	A
I _{FRMS}	RMS current			500	A
I _{FSM}	Surge forward current	Sine wave, 10 ms Without reverse voltage	25	6000	A
			180	5000	A
I ² t	I ² t	Sine wave, 10 ms Without reverse voltage	25	180000	A ² s
			180	125000	A ² s
V _F	Forward voltage	On-state current = 750A	180	1.30	V
V _{F(TO)}	Threshold voltage		180	0.85	V
r _F	Forward slope resistance		180	0.60	mΩ
MOUNTING					
R _{th(j-c)}	Thermal impedance, sin 180°	Junction to case		0.19	°C/W
R _{th(c-h)}	Thermal impedance	Case to heatsink		0.03	°C/W
T _j	Max. junction temperature			180	°C
T _{stg}	Storage temperature			-40 180	°C
M	Mounting torque			26	NM
W	Weight (Approx.)			250	gm
			Prepared by : ABA	Date of Publication : 25.03.2015	
			Approved by : RBS	Revision : 0	


DISSIPATION CHARACTERISTICS

SINE WAVE




FORWARD CURRENT DERATING CURVE

SINE WAVE




DISSIPATION CHARACTERISTICS

SQUARE WAVE



FORWARD CURRENT DERATING CURVE

SQUARE WAVE




Prepared by : ABA

Date of Publication : 25.03.2015


Approved by : RBS

Revision : 0


FORWARD CHARACTERISTIC



SURGE CHARACTERISTICS




TRANSIENT THERMAL IMPEDANCE



Prepared by : ABA	Date of Publication : 25.03.2015
Approved by : RBS	Revision : 0

Outline



MS Power GmbH
Mergenthalerallee 23A
65760 Eschborn, Deutschland
E-mail : info@msspowergroup.de

www.msspowergroup.com

Prepared by : ABA

Date of Publication : 25.03.2015

Approved by : RBS

Revision : 0

Terms & Conditions of usage :

The data contained in this product datasheet is exclusively intended for technically trained staff. You and your technical departments will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application. This product datasheet is describing the characteristics of this product for which a warranty is granted. Any such warranty is granted exclusively pursuant to the terms and conditions of the supply agreement. There will be no guarantee of any kind for the product and its characteristics. The information in the valid application- and assembly notes of the device must be considered.

Should you require product information in excess of the data given in this product datasheet or which concerns the specific application of our product, please contact the sales office, which is responsible for you (see www.mspowergroup.com). For those that are specifically interested we may provide application notes.

Due to technical requirements our product may contain dangerous substances. For information on the types in question please contact the sales office, which is responsible for you.

Should you intend to use the Product in aviation applications, in health or life endangering or life support applications, please notify. Please note, that for any such applications we urgently recommend

- to perform joint Risk and Quality Assessments;
- the conclusion of Quality Agreements;
- to establish joint measures of an ongoing product survey, and that we may make delivery dependent on the realization of any such measures.

If and to the extent necessary, please forward equivalent notices to your customers.

Changes of this product datasheet are reserved.

Prepared by : ABA	Date of Publication : 25.03.2015
Approved by : RBS	Revision : 0