



Key Parameters

V_{RRM}	= 1600V
$I_{F(AV)}$	= 420A
I_{FSM}	= 9000A
$V_{F(TO)}$	= 0.80V
r_F	= 0.45mΩ

Features

- Full blocking capability over wide temperature range
- Hermetic metal case with glass insulator
- Threaded Stud

Applications

- Power Supplies
- Uncontrolled Rectifiers
- Battery Chargers

Ordering Information

MS D	321	N	X X	M	B
Rectifier Diode	Current code	Polarity R= Stud Anode N= Stud Cathode	Voltage Code Code X 100 = V_{RRM}	Stud Threads M = Stud M24 X 1.5	Technology B = Solder Bond Technology
Order Code MS D321N16MB : 1600V V_{RRM} , M24 Stud, Diode with stud Cathode					

Prepared by : ABA

Date of Publication : 25.03.2015


Approved by : RBS

Revision : 0

Symbol	Characteristic	Conditions	Tj [°C]	Value	Unit
BLOCKING					
V _{RRM}	Repetitive peak reverse voltage		180	200 - 1600	V
V _{RSM}	Non-repetitive peak reverse voltage		180	300 - 1700	V
I _{RRM}	Repetitive peak reverse current	V= V _{RRM}	180	40	mA
CONDUCTING					
I _F (AV)	Mean forward current	180° sin ,50 Hz, T _c =100°C T _c =125°C		420 320	A
I _{FRMS}	RMS current			659	A
I _{FSM}	Surge forward current	Sine wave, 10 ms Without reverse voltage	25	9000	A
			180	8000	A
I ² t	I ² t	Sine wave, 10 ms Without reverse voltage	25	405 x 10 ³	A ² s
			180	320 x 10 ³	A ² s
V _F	Forward voltage	On-state current = 1000A	180	1.25	V
V _{F(TO)}	Threshold voltage		180	0.80	V
r _F	Forward slope resistance		180	0.45	mΩ
MOUNTING					
R _{th(j-c)}	Thermal impedance, sin 180°	Junction to case		0.15	°C/W
R _{th(c-h)}	Thermal impedance	Case to heatsink		0.015	°C/W
T _j	Max. junction temperature			180	°C
T _{stg}	Storage temperature			-40 180	°C
M	Mounting torque			32	NM
W	Weight (Approx.)			350	gm


DISSIPATION CHARACTERISTICS

SINE WAVE




FORWARD CURRENT DERATING CURVE

SINE WAVE




DISSIPATION CHARACTERISTICS

SQUARE WAVE



FORWARD CURRENT DERATING CURVE

SQUARE WAVE




Prepared by : ABA

Date of Publication : 25.03.2015


Approved by : RBS

Revision : 0


FORWARD CHARACTERISTIC



SURGE CHARACTERISTICS



TRANSIENT THERMAL IMPEDANCE




Prepared by : ABA

Date of Publication : 25.03.2015

Approved by : RBS

Revision : 0

Outline



MSpower
SEMICONDUCTOR

MS Power GmbH
Mergenthalerallee 23A
65760 Eschborn, Deutschland

E-mail : info@mspowergroup.de

www.mspowergroup.com

Prepared by : ABA

Date of Publication : 25.03.2015

Approved by : RBS

Revision : 0

Terms & Conditions of usage :

The data contained in this product datasheet is exclusively intended for technically trained staff. You and your technical departments will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application. This product datasheet is describing the characteristics of this product for which a warranty is granted. Any such warranty is granted exclusively pursuant to the terms and conditions of the supply agreement. There will be no guarantee of any kind for the product and its characteristics. The information in the valid application and assembly notes of the device must be considered.

Should you require product information in excess of the data given in this product datasheet or which concerns the specific application of our product, please contact the sales office, which is responsible for you (see www.mspowergroup.com). For those that are specifically interested we may provide application notes.

Due to technical requirements our product may contain dangerous substances. For information on the types in question please contact the sales office, which is responsible for you.

Should you intend to use the Product in aviation applications, in health or life endangering or life support applications, please notify. Please note, that for any such applications we urgently recommend

- to perform joint Risk and Quality Assessments;
- the conclusion of Quality Agreements;
- to establish joint measures of an ongoing product survey, and that we may make delivery dependent on the realization of any such measures.

If and to the extent necessary, please forward equivalent notices to your customers.

Changes of this product datasheet are reserved.

Prepared by : ABA	Date of Publication : 25.03.2015
Approved by : RBS	Revision : 0