

Current Transducer LT 4000-T/SP11

$$I_{PN} = 4000 \text{ A}$$

For the electronic measurement of currents : DC, AC, pulsed..., with a galvanic isolation between the primary circuit (high power) and the secondary circuit (electronic circuit).



Electrical data

I_{PN}	Primary nominal r.m.s. current	4000	A
I_p	Primary current, measuring range	0 .. ± 6000	A
R_M	Measuring resistance with $\pm 24 \text{ V}$	$R_{M \min}$	$R_{M \max}$
		@ $\pm 4000 \text{ A}_{\max}$	0 10 Ω
		@ $\pm 6000 \text{ A}_{\max}$	0 2 Ω
I_{SN}	Secondary nominal r.m.s. current	800	m A
K_N	Conversion ratio	1 : 5000	
V_C	Supply voltage ($\pm 5 \%$)	± 24	V
I_C	Current consumption	$30 + I_S$	m A
V_d	R.m.s. voltage for AC isolation test, 50 Hz, 1 mn	9 ¹⁾	k V
		1 ²⁾	k V
V_e	R.m.s. voltage for partial discharge extinction @ 50 pC		k V
		2.5	k V

Accuracy - Dynamic performance data

X	Accuracy @ $I_{PN}, T_A = 25^\circ\text{C}$	± 0.5	%
ϵ_L	Linearity	< 0.1	%
I_O	Offset current @ $I_p = 0, T_A = 25^\circ\text{C}$	Typ	Max
			± 0.8 m A
I_{OT}	Thermal drift of I_O - 40°C .. + 70°C	± 0.4	± 0.8 m A
t_r	Response time ³⁾ @ 90 % of I_{PN}	< 1	μs
di/dt	di/dt accurately followed	> 50	A/ μs
f	Frequency bandwidth (- 1 dB)	DC .. 100	k Hz

General data

T_A	Ambient operating temperature	- 40 .. + 70	$^\circ\text{C}$
T_S	Ambient storage temperature	- 50 .. + 85	$^\circ\text{C}$
R_S	Secondary coil resistance @ $T_A = 70^\circ\text{C}$	15	Ω
m	Mass	13	kg
	Standards	EN 50155	

Notes : ¹⁾ Between primary and secondary + shield

²⁾ Between secondary and shield

³⁾ With a di/dt of 100 A/ μs .

Features

- Closed loop (compensated) current transducer using the Hall effect
- Insulated plastic case recognized according to UL 94-V0.

Special features

- $V_d = 9 \text{ kV}^1)$
- $T_A = -40^\circ\text{C} \dots +70^\circ\text{C}$
- Shield
- Connection to secondary circuit on AMP CPC 13/9
- Burn-in
- Railway equipment.

Advantages


- Excellent accuracy
- Very good linearity
- Low temperature drift
- Optimized response time
- Wide frequency bandwidth
- No insertion losses
- High immunity to external interference
- Current overload capability.

Applications

- AC variable speed drives and servo motor drives
- Static converters for DC motor drives
- Battery supplied applications
- Uninterruptible Power Supplies (UPS)
- Switched Mode Power Supplies (SMPS)
- Power supplies for welding applications.

030204/1

Dimensions LT 4000-T/SP11 (in mm. 1 mm = 0.0394 inch)



Mechanical characteristics

- General tolerance ± 1 mm
- Transducer fastening 4 slots $\varnothing 10.5$ mm
4 M10 steelscrews
Fastening torque max. 11.5 Nm or 8.48 Lb. - Ft.
- Connection of primary 8 holes $\varnothing 13$ mm
- Connection of secondary AMP CPC 13/9

Remarks

- I_S is positive when I_p flows in the direction of the arrow.
- Temperature of the primary conductor should not exceed 100°C.