

ENVIRONMENTAL METER

Light Meter VA8050 / MS6610

VA8050



MS6610



Applications:
Public settings, light manufacturing,
photo studio, interior renovation,
construction, greenhouses



Specifications

	VA8050	MS6610
Range	0~30000 Lux (lm/m2)	0 ~ 2000 Lux
	0~2788.0 ftc (lm/ft2)	2000 ~ 19990 Lux
Accuracy	±(4%+50)	±5%
Resolution	1 Lux	1 Lux
Sample rate	0.1 ftc	10Lux/100Lux
Operating Environment	1 time / sec	1 time / sec
		0°C ~50°C (32 °F ~122 °F)
Storage Environment		0~80% RH
		-20°C ~60°C (-4 °F ~140 °F)
		0~80% RH

Features

Max. Display	9999	1999
Data Hold	✓	✓
Auto Power Off	about 20 minutes	
Low Power Indicator	✓	✓
Back Light	✓	
Max/Min Value	✓	
Wire Length		150 cm
Sensor Size		83 x 52 x 20.5 mm
Size	121 x 60x 30 mm	125.5 x 72 x 27 mm
Weight	~ 180g (including battery)	

Accessories Included	Free 1.5V x3 AAA batteries	9V 6F22 batteries
	Free protect cover	User Manual
	Free sturdy carrying case	
	Free Wrist strap	
	User Manual	

Fastron
Electronics

- Power Semiconductors
- Electrical Measurement
- Process Control

9B Lakewood Blvd
Braeside VIC 3195 Australia

Web: www.fastron.com.au
Email: sales@fastron.com.au
Telephone: + 61- 3 - 97635155
Facsimile: + 61- 3 - 97635206