

# ENVIRONMENTAL METER

## PH Meter / Conductivity Meter VA1020 / VA1021 / VA1022

VA1020



VA1022



Display with back light make reading clear even in dark

### Specifications

	VA1020	VA1020B	VA1021	VA1021B	VA1022	VA1022B
Range	0.0~14.0 pH				0~1999 uS/cm (0~1028 TDS / 0~999 mg/L)	
Temperature	0~50°C				0~50°C	
Accuracy	0.1pH/0.5°C		0.02pH/0.5°C		±2%/0.5°C	
Sensor	Internal		External(BNC)		Internal	
Bluetooth/App		✓		✓		✓
Power	3V(1.5V*2pcs AAA) up to 500hr				3V(1.5V*2pcs AAA) up to 500hr	
Size	153*40*38mm				153*40*38mm	
Weight	0.1Kg				0.1Kg	

### Features

Auto 3 adjustable points calibration (PH4.0, PH6.8, PH9.1)	uS/cm, TDS, mg/L & temperature double display
Automatic temperature compensation (°C and °F)	Automatic temperature compensation (°C and °F)
Data hold	Adjustable calibration point
LCD Display with back light	Low battery indication
Replaceable External Sensor (VA1021/VA1021B)	Data hold, Back light
IP65 water proof & pen clip	IP65 water proof & pen clip
Auto power off ~15 minutes	Auto power off ~15 minutes
Bluetooth with free App for Android optional (VA1020B/VA1021B)	Bluetooth with free App for Android optional (VA1022B)

**Fastron**  
Electronics

- Power Semiconductors
- Electrical Measurement
- Process Control

9B Lakewood Blvd  
Braeside VIC 3195 Australia

Web: [www.fastron.com.au](http://www.fastron.com.au)  
Email: [sales@fastron.com.au](mailto:sales@fastron.com.au)  
Telephone: + 61- 3 - 97635155  
Facsimile: + 61- 3 - 97635206