

PROCESS CALIBRATOR

Volt / mA & Thermocouple Calibrator VA701 / VA702

VA701

VA702



Key Features

- Be used to check measuring instruments of current, voltage and thermocouple
- Easy operation interface, numeric keypad input.
- Scan Mode / Programming Mode
- Store / recall 10 group setting.
- USB interface, the software supports remote control.
- Power: AAA*6 / External adapter (option)
- Size: 205x97x45mm
- Weight: ~460g (include battery)

Specifications

		Range	Resolution	Accuracy	VA701	VA702
Input / Output Voltage	20.00V	0~20.00 V	10mV	0.1%+5	✓	✓
	100.00mV	-10~100.00mV	10μV	0.1%+5	✓	✓
Input / Output Current	24.00mA	0~24.00mA	10μA	0.1%+3	✓	✓
Thermocouple	K(CA)	-200.0°C ~+1372.0°C	0.1°C	±0.7°C	N/A	✓
	J(IC)	-200.0°C ~+1200.0°C	0.1°C	±0.7°C		✓
	E(CRC)	-200.0°C ~+1000.0°C	0.1°C	±0.7°C		✓
	T(CC)	-200.0°C ~+400.0°C	0.1°C	±0.7°C		✓
	N	-250.0°C ~+1300.0°C	0.1°C	±0.9°C		✓
	S(PR10)	-20°C ~+1750°C	1°C	±2°C		✓
	R(PR13)	-20°C ~+1750°C	1°C	±2°C		✓
	B(PR30)	+600°C ~+1800°C	1°C	±2°C		✓

Fastron
Electronics

- Power Semiconductors
- Electrical Measurement
- Process Control

9B Lakewood Blvd
Braeside VIC 3195 Australia

Web: www.fastron.com.au
Email: sales@fastron.com.au
Telephone: + 61- 3 - 97635155
Facsimile: + 61- 3 - 97635206