

### Features:

- Isolated mounting base 3000V~
- Pressure contact technology with Increased power cycling capability
- Space and weight saving

### Typical Applications

- Various rectifiers
- DC supply for PWM inverter

$V_{RSM}$	$V_{RRM}$	Type & Outline
2300V	2200V	MD1293-22-432F2A

SYMBOL	CHARACTERISTIC	TEST CONDITIONS	$T_j(^{\circ}C)$	VALUE			UNIT
				Min	Type	Max	
$I_{F(AV)}$	Mean forward current	180° half sine wave 50Hz Single side cooled, $T_C=100^{\circ}C$	150			1293	A
$I_{F(RMS)}$	RMS forward current		150			2030	A
$I_{RRM}$	Repetitive peak current	at $V_{RRM}$	150			50	mA
$I_{FSM}$	Surge forward current	10ms half sine wave $V_R=0V$	150			40	kA
$I^2t$	$I^2t$ for fusing coordination					8000	$A^2s \cdot 10^3$
$V_{FO}$	Threshold voltage		150			0.70	V
$r_F$	Forward slope resistance					0.10	m $\Omega$
$V_{FM}$	Peak forward voltage	$I_{FM}=3000A$	25			1.35	V
$R_{th(j-c)}$	Thermal resistance Junction to case	Single side cooled per chip				0.038	$^{\circ}C/W$
$R_{th(c-h)}$	Thermal resistance case to heat sink	Single side cooled per chip				0.020	$^{\circ}C/W$
$V_{iso}$	Isolation voltage	50Hz, R.M.S, t=1min, $I_{iso}:1mA(max)$		3000			V
$F_m$	Terminal connection torque(M16)				12.0		N·m
	Mounting torque(M6)				6.0		N·m
$T_{stg}$	Stored temperature			-40		125	$^{\circ}C$
$W_t$	Weight				2700		g
Outline	432F2A						




Fig.1




Fig.2




Fig.3




Fig.4




Fig.5




Fig.6




Fig.7




Fig.8

Outline:

