

CHA-HT I Surface distribution box



Model Code	Outside Dimenstion (mm)			(KG)	(KG)	(只)	(cm)
	L	W	н	G. Weight	N. Weight	Qty/Carton	Carton Dimenstion
CHA-HT 5WAYS	115	150	90	13	11.9	40	49 × 33 × 48
CHA-HT 8WAYS	197	150	90	14.2	13.2	30	48×41.5×48.5
CHA-HT 12WAYS	250	193	105	16.3	15.3	20	52.5 × 40.5 × 57
CHA-HT 15WAYS	305	195	105	18.5	17.5	20	63 × 40.5 × 57
CHA-HT 18WAYS	360	198	105	20.4	19.4	20	74 × 40.5 × 57
CHA-HT 24WAYS	270	350	105	14.6	13.6	10	56.5 × 36.5 × 56.5





Body material: ABS

Transparent door: PC

Material characteristics: Impact, heat, low temperature and chemical resistance, excellent electrical performance and surface gloss, etc.

Certificates: CE, ROHS

Protection grade: IP65

Application: Suitable for indoor and outdoor electric, communication, fire fighting apparatus, iron and steel smelting, petrochemical industry, electron, power system, railway, building, mine, air and sea port, hotel, ship, works, waste water treatment equipment, environmental equipment and so on.

Installation: 1, Inside: There are din rail inside for din-rail type circuit breakers, earth bar and natural bar for cable connection.

> Outside: The products can be directly fixed on the wall or other flat boards with screws or nails via the screw holes in the base.

Outlet hole: The plastic plate in the hole can be knocked off for cables.





CHA-HT